35-078-31
DUNN QUADRAHGLE

100 NORTH CAROLINA
N3515-47830/15
DIAGRAM NI 17-3
RALEIGH

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Cumberland, Harnett, Johnston and Sampson Counties


Final adjustment of 1973

Edition of 10/28/75

PR: DSW/jyk

NGVD 29

GARNER (145)



MGS (USCRGS) VERTICAL CONTROL DATA

A. Quadrangle 350783

DUHN QUADRANGLE

35-078-31 N3515-W7830/15 108 NORTH CAROLINA

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE HO.	H. C. GEODETIC SURVEY	PAGE NO.
188 ADJ 1903	3	113	. 5
PTS NO 22 207 ADJ 1903	3 3	LAMB 1965	8
210 ADJ 1903	3	ALLEN 1972	10
220 ADJ 1903	3	BEH-RAL 1972	8
239 ADJ 1903	3 3 3 3 3,3	BLALOCK 1972	10
PTS NO 21 243 ADJ 1903	3	CRABAPPLE 1972	7
TT 9 WAC 1946 112	3,3	CREEK 1972	10
142 WSM 1955 120	4	DIXIE 1972	8
143 WSM 1955 143	4,4	EMORY 1972 NGVD 29	7
149 WSM 1955 148	4	EHHIS 1972 Elevations	7,8
1 MAX 1972 299	8	FORK 1972	11
2 MAX 1972 314	8	HOWARD 1972	6
3 MAX 1972 193	. 9	JAYNAT 1972	. 7
4 MAX 1972 217	9	MABRY 1972	10
6 MAX 1972 145	5	McLAMB 1972	7
10 MAX 1972 199	5	PARRISH 1972	10
20 1214 277	•	PLUM 1972 \	6
USED-AWAY MAP SERVICE		RING 1972	10
Charles and the Control of the Contr		RYLES 1972	6
BM DN2 1954	8	SCH00L 1972	6,9
BM DN3 1964	. 9	SHALLOW 1972	6
BM SN7 1964	5	STEPHENSON 1972	11
811 SN8 1964	5	VERDIE 1972	. 7
		WALKER 1972	9
NGS		WALNUT 1972	7
		WALTER 1972	6
BENSON 1934	8	WEDDING 1972	9
E 70 1934	5	WILLIAMS 1972	10
BENSON 1949	Ź		
0 93 1935	ıi		
LUKE 1972	12		

·			3	35-078-31 3
DUNN Bulletin 646	108 NORTH CA	ROLINA	T. A. Green	ŕ
ISOLATED BENCH MARKS (By T. A. Green, 1905; Bu	ulletin 646)	NGVD 29 Elevations	1905	<u>Feet</u>
"239 ADJ 1903" (Destroyed, 1972)		-iovalions		239-479
Four Oaks, 4.4 mi SW. of; W. of rd. at crossin stamped "188 ADJ 1903" (Reported not found,		tracks; on iron post;	standard cap	187.599
Benson; at SE. corner on E. side of hotel kept cap stamped "PRIM TRAV STA NO 21 243 ADJ 190			ost; standard	242.736
Benson; 3.4 mi SE. of; on W. side of rd. at cr standard cap stamped "210 ADJ 1903"	rossroad; near l	arge walnut tree; on	iron post;	210.417
Mix, 0.4 mi W. of; on E. side of rd. at crossr (Not found, 1964)	road; on ir on po	st; standard cap stam	iped "220 ADJ 1903"	220.598
Mingo, just N. of; E. of rd. N. of forks; on i "PRIM TRAV STA NO 22 207 ADJ 1903" (Not fou		ard cap stamped		207.648
	LINE 1.			•
J. R. Rigby, 1946; Book V 262				
U.E., Linden, 0.9 mi N. of, along State Highwa mi W. along dirt rd.; about 600 ft E. of RR. center of rd.; 19 ft W. of field rd. S.; in	crossing; 450	ft MM. of frame house	; 31 ft N. of	121.85
Linden, 1.3 mi N. of, along State Highway 217; 22.5 ft W. of center of rd.; on bank 4 ft hi projecting 0.4 ft.; standard tablet stamped	gher than rd.;	in plowed field; in c	oncrete post	112.732
Reference mark; 180 ft N. of tablet; about 300 Highway 217; in W. side of telephone pole; re		ling; 39 ft W. of cen	ter of State	111.85
	ITHE 2			

LINE 2.

W. S. Monk, 1955; Book AV 432

Ì	1	0.00	Linden, 1.3 mi N. of, along State Highway 217; 0.3 mi N. of crossroad; 0.3 mi S. of crossing, Little River, 22.5 ft W. of centerline of rd.; on bank 4.0 ft higher than rd.; in plowed field; in concrete post projecting 0.4 ft.; standard tablet stamped "TT 9 WAC 1946 112"	
			(Reported not found, 1972) (Also described in line 1)	112.73?
1	1	0.82	U.E., 170 ft W.and 60 ft S. of, and 1 ft above T-rd. S.; in face on N. side of 26-in. oak; rail spike	132.63

LIN	E 2 (Cont'd.)		Feet
1	3	1.54	U.E., 30 ft S. and 20 ft E. of, and level with woods rd. E.; in root on W. side of 24-in. oak; copper nail and washer	126.97
1	5	2.72	Reference mark; 600 ft S. of tablet; in root on E. side of 18-in. oak; copper nail and washer	124.34
1	6	2.84	Bunnlevel, 2.3 mi E. of, thence 1.7 mi S.; 105 ft E. and 41 ft N. of, and 2 ft lower than crossroad; 8.0 ft S. of ditch; 4-1/2 ft NW. of 24-in. pine; 4-1/2 ft NE. of 24-in. pine; in concrete post; standard tablet stamped "142 WSM 1955 120"	120.325
1	7	3.34	U.E., 55 ft NE., and 1 ft above junction of lane NE.; in face on S. side of 2-in. oak; rail spike	128.58
1	8	3.90	U.E., 120 ft S. and 175 ft W. of, and level with lane W.; 15 ft S. of SE. corner of tobacco barn; in root on E. side of 12-in. oak; copper nail and washer	131.31
1	9	4.55	Reference mark; 35 ft E. of tablet; on E. end of concrete pipe culvert; chiseled cross	141.60
1	10	4.55	Bunnlevel, 2.3 mi E. of; 250 ft S. and 19 ft W. of, and 2.0 ft lower than I-rd. S.; 3.0 ft N. of power pole; in concrete post; standard tablet stamped "143 WSM 1955 143"	142.687
			LINE 3.	
₩.	S. Mor	nk, 1955; Book	NGVD 29 Elevations	
1	56	0.00	"143 WSM 1955 143" (Described in line 2)	142.687
1	57	1.01	U.E., SE. of wood bridge crossing Upper Little River; on SE. end of concrete retaining wall; chiseled cross	115.41
1	58	1.62	Bunnlevel, 2.1 mi E. of, thence 1.5 mi N.; 0.6 mi N. of crossing Upper Little River; 40 ft N.and 35 ft E. of, and 4.0 ft above crossroad; 18.0 ft W. of power pole; in concrete post; standard tablet stamped "149 WSM 1955 148" (Reported disturbed, 1972)	148.224
1	59	1.79	Reference mark; 880 ft N. of tablet; 50 ft E. of rd.; and 12 ft S. of drive; in root on W. side of 12-in. oak; copper nail and washer	159.16

	フフ・ロノケーフェ
:	5

108 NORTH CAROLINA

.contit

Book AV 1650

1072

Max. K. Weber

			1972	
			TINE 4.	Feet
Мэ	v K. W	eber, 1972; E	Rook AV 1650	
110	A N. H	00019 13129 1	NGVD 20	. '
1	42	0.00	"E 70 1934" (NGS) Elevations	149.885
1	42	0.62	U.E., top of C. rail opposite MP 189	157.50
1	43	1.36	Dunn, 2.2 mi SW. of, along railroad; at Long Branch Road crossing; 79.2 ft SSW. of grade crossing of northbound tracks; 7.5 ft ESE. of E. rail of northbound tracks; in drill hole on NW. corner of 2-1/2 by 2-1/2 ft concrete base of semaphore; USED — Army Map Service standard disk stamped TBM SN8 1964"	182.165
1	44	1.74	U.E., in centerline of crossroad (Highway 301 and Long Branch Road) (1002 and 1780)	180.87
1	45	2.54	Ounn, 2.3 mi SW. of junction of Highways 301 and 421, thence 0.8 mi SE. along Route 1002 (Long Branch Road); 70.4 ft N. of centerline of overpass bridge over southbound lanes of Interstate Highway 95; 13.0 ft NE. of centerline of Route 1002 at NW. end of overpass bridge; in drill hole on concrete guard of bridge; USED — Army Map Service standard disk stamped "BM SN7 1954"	196.064
	46	3.59	Dunn, 2.3 at Sw. of junction of Highways 421 and 301, thence 1.85 mi SE. along Route 1002; 109.4 ft W. of I-rd. NW.; 66.7 ft NE. of NE. corner of white frame house; 45.6 ft SSW. of Route 1002; 1.8 ft NW. of power pole No. 4564; in concrete post projecting 0.1 ft.; standard tablet stamped "5 MAX 1972 145"	144.615
1	47	3.84	U.E., on M. corner of ME. concrete guardrail of bridge over Mingo Swamp; chiseled square (NOTE: This chiseled square was originally made by some other agency, possibly A.M.S.)	144.60
			∑ogs into Stedman quadrangle/	
1	52	8.32	Dunn, 5.1 mi SE. of center of, along Highway 421, thence 1.0 mi E. along Route 1627, thence 0.1 mi NE. along Route 1626; 1.2 mi E. of Plainview School; 21.1 ft W. of centerline of bridge; 12.6 ft NW. of centerline of rd. at SW. and of bridge; 1.2 ft NE. of SW. and of concrete guardrail; in drill hole on guardrail; standard tablet stamped "10 MAX 1972 199"	198.821
1	53	9.08	U.E., in centerline of rd. at drive S.; copper nail and washer (NOTE: Westernmost of two circling house)	211.82
			LINE 5.	
Мах	K. We	ber, 1972; B	ook AV 1650	
1	1	0.00	Coats; 80 ft MM. of MM. corner of brick building; 49.3 ft NE. of NE. corner of railway station building; 22.3 ft M. of centerline of Railroad Street; 16.1 ft E. of E. rail; in concrete post flush with ground; North Carolina Geodetic Survey standard disk stamped "113" (Elevation by USGS) (Reported disturbed, 1972)	314.084

35.	-078	-31
		6

109	NUSTR	CAROLINA	ı

DUNN

NGVD 29 Elevations

LINE 5 (Cont'd.)						
1	2	0.30	Coats; 0.35 mi N. of post office, along Railroad Street; 60 ft NE. of Interstate Highways 55 and 27; 20.0 ft N. of centerline of Highway 27; 9.6 ft SE. of power pole; 9.3 ft W. of E. rail; in concrete post flush with ground; North Carolina Geodetic Survey standard disk stamped "SCHOOL 1972"	299-955		
1	3	0.55	Coats; 0.35 mi N. of post office, along Railroad Street, thence 0.25 mi E. along Highway 27; 159.5 ft WNW. of I-rd. N.; 85.7 ft SW. of SW. corner of frame house; 23.7 ft S. of 14-in. pine tree with aluminum reference tag; 16.5 ft N. of centerline of Highway 27; 12.6 ft W. of centerline of dirt drive; in concrete post buried 0.2 ft.; North Carolina Geodetic Survey standard disk stamped "WALTER 1972"	307.165		
1	4	0.96	Coats; 0.35 mi N. of post office, along Railroad Street, thence 0.65 mi E. along Highway 27; 100 ft WSW. of Y-rd. intersection; 65.1 ft MV. of power pole with aluminum reference tag; 53.0 ft N. of NW. corner of frame house; 17.2 ft S. of centerline of Highway 27; in concrete post buried 0.4 ft.; NCGS standard disk stamped "HOWARD 1972"	285.184		
1	5	1.33	Coats; 0.35 mi N. of post office, along Railroad Street, thence 1.0 mi E. along Highway 27; 62.4 ft NE. of NE. corner of cinderblock wall; 47.8 ft SSE. of concrete right-of-way marker; 18.5 ft N. of centerline of Highway 27; 18.0 ft SE. of centerline of farm rd.; 8.4 ft N. of N. edge of pavement; in concrete post buried 0.4 ft.; NCGS standard disk stamped "RYLES 1972"	244.141		
1	6	2.10	U.E., centerline of Highway 27 over drain (Easternmost of three at concrete culverts)	203.57		
			WL = 193.6			
1	7	2•72	Coats; 0.35 mi N. of post office, along Railroad Street, thence 2.4 mi E. along Highway 27; 253 ft SE. of crossroad; 34.4 ft NNW. of 8-in. pine with aluminum reference tag; 31.4 ft S. of centerline of Highway 27; 23.0 ft NE. of forked red oak tree with aluminum reference tag; on 5-ft bank that appears to be old rd. bed; in concrete post projecting 0.2 ft.; NCGS standard disk stamped "SHALLOW 1972"	248.353		
1	8	3.06	Coats, 0.35 mi N. of post office, along Railroad Street, thence 2.75 mi E. along Highway 27; 100 ft NW. of I-rd. N. (27 and 1560); 88 ft W. of centerline of Route 1560; 32.4 ft N. of centerline of Highway 27; 9.7 ft SE. of power pole; 2.0 ft N. of edge and on top of 10-ft bank; in concrete post projecting 0.2 ft.; NCGS standard disk stamped "PLUM 1972"	238.012		

NGVD 29 Elevetione

	LI	NE 5 (Cont'd.)		Feet
	1	9	3.44	Coats; 0.35 mi N. of post office, along Railroad Street, thence 3.15 mi E. along Highway 27; 45 ft NE. of crossroad; 37 ft E. of centerline of Route 1561; 28.2 ft N. of centerline of Highway 27; in concrete post projecting 0.1 ft.; NCGS standard disk stamped "VERDIE 1972"	245•815
	1	10	3.78	Coats; 0.35 mi N. of post office, along Railroad Street, thence 3.5 mi E. along Highway 27; 0.35 mi E. of crossroad (Highway 27 and Route 1561); 61.5 ft EffE. of 3-ft red oak tree; 48.2 ft WSW. of 4-in. red oak tree; 22 ft N. of centerline of hwy. at drive NE.; 17 ft NW. of centerline of drive; 14 ft NE. of centerline of Highway 27; in concrete post buried 0.4 ft.; NCGS standard disk stamped "JAYMAT 1972"	254•737
	1	11	4.65	Coats; 0.35 mi N. of post office, along Railroad Street, thence 4.35 mi E. along Highway 27; 3.3 mi W. of center of Benson; on 7-ft bank diagonally across intersection from J. L. Adams Grocery; 88.7 ft SE. of stop signpost with aluminum reference tag; 83.0 ft E. of crossroad; 41.3 ft NE. of Highway 27; 31.5 ft S. of power pole; in concrete post projecting 0.3 ft.; NCGS standard disk stamped "ENNIS 1972"	26½ . 586
	1	12	5.05	Benson, 2.9 mi W. of center of, along Highway 27; 2.25 mi W. of junction of Highways 50 and 27; 300 ft SSE. of crossroad (Highway 27 and 1551 North - 1705 South); 127.5 ft NM. of telephone cable junction box; 30.6 ft SW. of centerline of hwy.; in concrete post 2 ft higher than rd. and flush with ground; NCGS standard disk stamped "EMORY 1972"	276.901
	1	13	5.41	Benson; 1.85 mi W. of junction of Highways 27 and 50, at W. edge of; 0.1 mi E. of Community Grocery store; 78.1 ft N. of IM. corner of brick house; 37.4 ft WMW. of centerline of driveway; 30.3 ft N. of crabapple tree; 26.0 ft SSW. of centerline of Highway 27; in concrete post flush with ground; ICGS standard disk stamped "CRABAPPLE 1972"	283.600
HAKNE		14 <i>OO</i>	5•83	Benson; 1.45 mi W. of junction of Highways 50 and 27, at W. edge of; 562 ft W. of I-rd. S. (Highway 27 and Route 1709); 93.0 ft NW. of power pole with aluminum reference tag; 37.2 ft S. of centerline of Highway 27; 12.0 ft E. of drainage ditch; in concrete post 4 ft higher than rd. and flush with ground; standard tablet stamped "WALNUT 1972"	258•937
JOHNST	1	15	6.75	Benson; 0.5 mi W. of junction of Highways 50 and 27, at W. edge of; 71 ft W. of centerline of hwy. at drive S. to Jack E. McLambs house; 18 ft N. of water meter cover; 16.5 ft NE. of 12-in. pine tree; 13.3 ft S. of centerline of hwy.; 3.3 ft S. of edge of pavement; in concrete post buried 0.2 ft.; NCGS standard disk stamped 'McLAMB 1972"	259.387 19.06
	1	16	7.27	Benson; in angle formed by intersection of State Highways 27 and 50; 209 ft NN. of intersection; 142 ft SN. of center of Highway 50; 52 ft N. of center of Highway 27; 20 ft N. of white witness post; in concreto 1.2 ft below ground; HGS standard triangulation station disk stamped "BENSON 1949"	254.446 8 0.603

AROLINA NGVD 29 Elevations

LIN	E 5 (Cont'd.)		Feet
1	17	7•29	Benson, 0.65 mi W. of center of; at junction of Highways 50 and 27; 92.7 ft NE. of NGS Triangulation Station BENSON reference mark No. 2; 25.0 ft N. of centerline of Highway 27; 11.3 ft S. of power pole with reference tag; 3.0 ft N. of S. tip of traffic island; in concrete post flush with ground; NCGS standard disk stamped "BEN-RAL 1972"	265•993
1	18	7.56	Benson, 0.4 mi W. of center of; 0.25 mi E. of junction of Highways 50 and 27; 60.3 ft NW. of power pole with aluminum reference tag; 46.0 ft W. of top of concrete signpost; 42.6 ft N. of top of concrete signpost; 33.2 ft SE. of 14-in. maple tree with aluminum reference tag; 24.0 ft W. of centerline of McLamb Street; 21.2 ft SE. of top of fire plug; 21.0 ft N. of centerline of West Main Street; 4.7 ft SW. of 12-in. maple with aluminum reference tag; in concrete post flush with ground; NCGS standard disk stamped "LAMB 1965"	261.634
1	19	7.94	"BENSON 1934" (NGS)	245.718
			LINE 6.	74.895
May	K. We	eber, 1972; Bo		
				all mal
1	21	0.00	"ENNIS 1972" (NCGS) (Described in line 5)	264.586
1	21	0.34	Benson, 2.95 mi W. of center of, along Highway 27, thence 0.5 mi N. along Route 1551; 117.2 ft NW. of NW. corner of abandoned cinderblock store building; 69.4 ft N. of T-rd. N. at offset crossroad; 43.0 ft NE. of Route 1551; 30.1 ft NW. of Route 1703; in concrete post projecting 0.2 ft.; NCGS standard disk stamped "DIXIE 1972"	279.669
1	22	1.11	Benson, 2.95 mi W. of center of, along Highway 27, thence 1.25 mi N. along Route 1551; about 350 ft SE. of crossroad; 58.8 ft NE. of centerline of rd. at drive E.; 55.1 ft E. of centerline of Route 1551; 34.2 ft NNE. of NW. corner of brick wall; 19.1 ft N. of centerline of drive; in concrete post projecting 0.2 ft.; standard tablet stamped "I MAX 1972 299"	299-199
1,	23	2•42	Benson, 2.95 mi W. of center of, along Highway 27, thence 2.6 mi N. along Route 1551; 94.0 ft NW. of crossroad; 84.8 ft N. of Route 1558; 56.4 ft W. of Route 1551; 18.3 ft SE. of center of well; across rd. from Weeks and Creech Grocery and at site of dismantled cotton gin; in drill hole in approximate center of 4-1/2 by 6-ft concrete slab projecting 1 ft.; standard tablet stamped "2 MAX 1972 314"	314.256
1	24	3.19	Benson, 2.95 mi W. of center of, along Highway 27, thence 3.35 mi N. along Route 1551; 2.3 mi S. of Hardee Crossroads; 89.6 ft E. of telephone cable; junction box; 26.0 ft E. of Y-rd.; 25.6 ft S. of ditch leading W. from field; 6.4 ft W. of W. edge of cultivated field; 4.4 ft N. of county line sign; in concrete post projecting 0.3 ft.; USED - Army Map Service standard disk stamped "BM DN2 1964"	298.405

				22-010-21
	DUNN		108 NORTH CAROLINA NGVD 29 Elevations	9
LIN	E 6 (Cont'd.)	·	Feet
1	27	4.52	Hardee Crossroads, 0.95 mi S. of, along Route 1309; 6.5 airline miles NW. of center of Benson; 61.3 ft E. of centerline of rd. at drive E.; 58.1 ft NNW. of NE. corner of house; 33.0 ft S. of yard fence; 8.3 ft N. of centerline of drive; 1.6 ft N. of power pole; in concrete post projecting 0.2 ft.; standard tablet stamped "3 MAX 1972 193"	193•224
1	28	4.80	U.E., in centerline of T-rd. W.; copper nail and washer (Intersection of Routes 1309 and 1310)	213.07
1	29	5.48	Hardee Crossroads, 109.5 ft NW. of crossroad; 46.2 ft W. of centerline of Route 1309; 3.8 ft NE. of E. corner of Duval Weeks Grocery store; in drill hole on SE. side of 2- by 2-ft concrete base of American Oil Company sign; standard tablet stamped "4 MAX 1972 217"	217.174
1	30	6.03	U.E., in centerline of small bridge; copper nail and washer (Route 1309 at McCullens Bridge)	171.35
1	31	6.61	Hardee Crossroads, 1.15 mi N. of, along Route 1309; 44.2 ft W. of I-rd. E. (1309 and 1322); 12.0 ft NW. of centerline of 10-ft ditch leading SW. into woods; 4.6 ft NE. of rail spike in 12-in. pine tree; in concrete post projecting 0.2 ft.; USED — Army Map Service standard disk stamped "PM DN3 1964"	194•073
			LINE 7.	
t4ax	K. We	eber, 1972; B	ook AV 1650	
1	57	0.00	"SCHOOL 1972" (NCGS) (Described in line 5)	299.953
1	57	0.83	U.E., in centerline of 1-rd. NE.; copper nail and washer (Highway 55 and Route 1547)	291.24
1	58	0.88	Coats; 0.85 mi N. of junction of Highways 55 and 27; about 250 ft N. of Highway 55 intersection with Route 1547; 186.7 ft N. of grade crossing; 111.9 ft NNE. of 16-in. chinaberry tree with aluminum reference tag; 87.7 ft E. of centerline of Highway 55; 44.5 ft W. of W. rail; 4.7 ft E. of SE. corner of cinderblock building; in concrete post; NCGS standard disk stamped "WALKER 1972"	290.493
1.	59	1.95	Coats; 1.95 mi N. of intersection of Highways 55 and 27; 136.9 ft ENE. of centerline of Highway 55; 107.6 ft WSW. of 18-in. pecan tree; 106.6 ft E. of telephone pole; 72.7 ft ENE. of E. rail; 18.2 ft SSE. of power pole with transformer and three guy wires; 13.1 ft SSE. of telephone cable junction box; 9.9 ft NKW. of centerline of EW. lane; in concrete post prejecting 0.2 ft.; NCGS standard disk stamped "WEDDING 1972"	321.985

35-078-31

,		•	3	5-0 78-31
	DUNN	÷.	108 NORTH CAROLINA NGVD 29 Elevations	10
LI	IE 7 (0	ont'd.)		Feet
	60	2.61	Coats; 2.6 mi N. of intersection of Highways 55 and 27, along Highway 55; 64.1 ft ESE. of T-rd. E.; 62.9 ft E. of centerline of Highway 55; 16.7 ft SW. of grade crossing; 12.2 ft S. of centerline of Route 1565; 8.7 ft W. of W. rail; in concrete post projecting 0.1 ft.; NCGS standard disk stamped "RING 1972"	329.206
1	61	2.90	Coats; 2.9 mi N. of intersection of Highways 55 and 27, along Highway 55; 87.0 ft E. of centerline of hwy. at drive E.; 65.5 ft W. of power pole with aluminum reference tag; 13.9 ft NE. of grade crossing; 9.7 ft N. of centerline of drive leading to Earl Parrish residence; 8.8 ft E. of E. rail; in concrete post flush with ground; NCGS standard disk stamped "PARRISH 1972"	329.079
1	62	3.41	Coats; 3.4 mi N. of intersection of Highways 55 and 27, along Highway 55; 127.0 ft E. of crossroad (55 and 1006); 70.0 ft NE. of centerline of Highway 55; 4.0 ft WSW. of "Thomas Allen Jr.'s" tombstone; 1.4 ft N. of S. edge of cemetery; in concrete post flush with ground; NCGS standard disk stamped "ALLEN 1972"	326.090
1	63	3 . 78	Coats; 3.75 mi N. of intersection of Highways 55 and 27, along Highway 55; 113.0 ft SE. of centerline of drive; 56.6 ft ESE. of E. corner of small frame house; 51.4 ft N. of hickory tree with aluminum reference tag; 35.4 ft SW. of centerline of Highway 55; 17.4 ft HE. of power pole with aluminum reference tag; in concrete post flush with ground; NCGS standard disk stamped "BLALOCK 1972"	319.935
1	64	4.23	Coats; 4.2 mi N. of intersection of Highways 55 and 27, along Highway 55; 0.8 mi NW. of Route 1006; 140.0 ft SE. of power pole; 29.7 ft NE. of centerline of Highway; 10.7 ft NW. of centerline of field rd.; 2.7 ft SW. of fenceline; in concrete post projecting 0.2 ft.; NCGS standard disk stamped "CREEK 1972"	266.169
1	65	4.93	Coats; 4.9 mi NV. of intersection of Highways 55 and 27, along Highway 55; 3.1 mi SE. of junction of Highways 210 and 55 at Angier; 98.4 ft S. of S. corner of Mabry's Store; 50.0 ft S. of hwy. at drive SW. to brick rambler; 45.3 ft SE. of centerline of drive; 23.5 ft NE. of power pole with aluminum reference tag; 20.8 ft SW. of centerline of hwy.; in concrete post buried 0.3 ft.; HCGS standard disk stamped "MABRY 1972"	324.065
1	66	5.50	U.E., in Y-rd. SW. (Highway 55 and Route 1538); copper nail and washer	284.850
1	67	5.83	Angior; 2.2 mi SE. of intersection of Highways 210 and 55, along Highway 55; 88.0 ft N. of Y-rd. W. (junction 55 and 1543); 34.5 ft S. of telephone pole with aluminum reference tag; 33.1 ft E. of centerline of hwy. at drive NE.; 11.8 ft SE. of centerline of drive; 5.4 ft NE. of drainage ditch; in concrete post flush with ground; NCGS standard disk stamped "WILLIAMS 1972"	294.047

108 NORTH CAROLINA

DUNN	108 HORTH CAROLINA	NGVD			
LINE 7 (Cont'd.)		NGVD 29 Elevations	Feet		
1 68 7.10	Angier; 0.9 mi S. of intersection of Highways 210 and 55; about 200 ft S. of intersection of Highway 55 and ft HW. of power pole with lamp and aluminum reference N. of power pole No. 6 with aluminum reference tag; 73 centerline of Route 1542 at drive W.; 64.3 ft W. of ce 55; 49.8 ft NE. of fence corner; 13.6 ft E. of centerline concrete post buried 0.3 ft.; NCGS standard disk st	Route 1542; 93.2 tag; 87.0 ft .1 ft N. of nterline of Highway ine of Route 1542;	303•486		
1 69 7.29	Angier; 0.7 mi S. of intersection of Highways 210 and 55; at NW. corner of cemetery and across hwy. from ser 123.0 ft S. of intersection of Highway 55 and Route 15 of S. end of gas pump island; 63.2 ft WNW. of 12-in. e with aluminum reference tag; 29.7 ft E. of centerline 23.1 ft S. of telephone pole with aluminum reference t post projecting 0.2 ft.; NCGS standard disk stamped "S	vice station; 07 W.; 66.1 ft ENE. 1m tree in cometery of Highway 55; ag; in concrete	312.696		
	LINE 8.				
By Max K. Weber, 1972; Book AV 1650					
1 38 0.00	"D 93 1935" (KGS)		287.142		
1 38 0.81	Coats, 0.45 mi S. of post office; 83.6 ft E. of State 17.4 ft W. of power pole with aluminum reference tag; E. rail; in concrete post flush with ground; 1865 stand triangulation station disk stamped "LUKE 1972"	7.8 ft E. of	290.209		