MTRO-ORDER LEVELING SEA LEVEL DATUM OF 1929

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RAEFORD QUADRANGLE MORTH CAROLINA N3445-17900/15 DIAGRAM NI 17-6 FLORENCE

Cumberland, Hoke and Robeson Counties

Final adjustment of 1972


Edition of 2/7/72

PR: WSM/jyk

NGVD 29 Elevations

CLIFDALE (73)

LAURINBURG (46)



ST PAULS (44)

PEMBROKE (30)

MGS (USC&GS) VERTICAL CONTROL DATA

A. Quadrangle 340791

# INDEX OF PERMANENT MARKS

		•	
MARK (USGS)	PAGE NO.	USED	PAGE 110.
TT 24 FLS 1946 219	. 3	BN 41	3
TT 25 1946 212	· <b>Å</b>	II A.95 25	3
TT 26 FLS 1946 219	4	3 TT A 9576	4
53 WSH 1949 225	4		
54 WSH 1949 231	5	NORTH CAROLINA GEODETIC SURVEY	
69 WSM 1949 213 NF, PO,	01-89 USGS 6		
55 WSH 1949 225	5	. MC 96	3
56 REW 1951 186	6,13	NC 351	4
57 REW 1951 164		•	
108 HLZ 1971 177	. 7	IIGS	
109 HLZ 1971 188	. 7		
110 HLZ 1971 155	. У	A 74 1935	3
111 HLZ 1971 183	7	U 74 1935	12
112 HLZ 1971 184	8,9	v 74 1935	12
113 HLZ 1971 190	. 8	Z 74 1935	5,5
114 HLZ 1971 196	9	RAEFORD 1935	3,3
126 HLZ 1971 198	9.	HODGIN 1949	5,11
127 HLZ 1971 194	9	HODGIN 1949 (AZ. MK.)	5
128 HLZ 1971 197	, 10	HODGIN NO 1 1949	5
129 HLZ 1971 217	10	HODGIN 110 2 1949	5
130 HLZ 1971 208	10,11	LUNBER BRIDGE 1949	13
131 HLZ 1971 205	10	PARKTON 1949	13
132 HLZ 1971 223	10	PARKTON 1949 (AZ. NK.)	13
133 HLZ 1971 193	11,12	PARKTON NO 1 1949	13
134 HLZ 1971 214	11	PARKTON 110 2 1949	. 13
135 HLZ 1971 217	12	PHIL 1949	8
136 HLZ 1971 201	12	PHILADELPHUS 1949	8
56 WEM	, 5	PHILADELPHUS NO 1 1949	8
		PHILADELPHUS NO 2 1949	8

NGVD 29 Elevations

Book V 262 a

Book V 262 a	2017	
LINE 1.	1946 <u>Fee</u> t	<u>t</u>
R. L. Beitle, 1946; Book V 262 a	NGVD 20	
"A 74 1935" (NGS)	Elevations 258-29	93
"RAEFORD 1935" (NGS)	262.11	16
Raeford; about one block N. of courthouse; 0.3 mi N. of Aberdeen-Raeford; about one block N. of courthouse; 0.3 mi N. of Aberdeen-Raeford; about one dirt street W.; 3.4 ft SM. of powerline poof storm drain; in concrete post 6 in. under pile of dirt. North standard disk stamped "NC 96"	le; 3 ft directly W. of S. end	76
Raeford; 1.0 mi N. of post office, along paved and unpaved street, dirt rd. to rd. forks; 30 ft SW. of center of NWSE. rd.; 24 ft 10 ft SW. of three-pronged tree; 10 ft W. of row of mailboxes; is 0.3 ft above ground; USED standard disk stamped "TT A 95 26"	SE. of center of NESW. rd.;	00
LINE 2.		
R. L. Beitle, 1946; Book V 262 a		
"RAEFORD 1935" (NGS) (Also in line 1)	262.11	16
U.E., Reeford; 0.6 mi E. of RR. station; 140 ft N. of center of U. 47 ft W. of SW. corner of tombstone inscribed "Johnson"; at W. e graves; in top of granite post; NGS standard magnetic station di	dge of dim rd. leading to	77
U.E., Raeford; 1.0 mi E. of RR. station; 0.7 mi SW. along U. S. Hi Rockfish Creek; 141 ft SW. of SW. corner of white stucco cottage on top of 4- by 4-in. concrete hwy. boundary post; chiseled squa	50 ft N. of center of rd.;	8
Raeford; 2.2 mi ENE. of post office, along U. S. Highway 15A to ju 25 ft W. of center of hwy.; in line with macadam rd.; 6 ft SE. o concrete post projecting 0.5 ft above ground; USED standard disk	f two 15-in. pine trees; in	00
U.E., Raeford; 2.1 mi NE. of post office, along U.S. Highway 15A thence 0.3 mi NE. along macadam rd. to junction of single lane detector of macadam rd.; 20 ft W. of center of dirt rd.; in concreground; iron pipe	irt rd. NE.; 30 ft N. of	00
U.E., Raeford; 2.1 mi E. of RR. station, along U. S. Highway 15A, rd.; 47 ft N. and 72 ft W. of junction of Ird. N.; in root on S copper nail and washer	•	3
Raeford; 2.1 mi NE. of post office, along U. S. Highway 15A, thence graded rd.; 0.7 mi ENE. of bridge over Beaver Creek; 44 ft N. and Ferd. N.; in concrete post; standard tablet stamped "TY 24 FLS 2"	f 53 ft E. of junction of	80

RAEFORD Book V 262 a NORTH CAROLINA

NGVD 29 Elévalions

R. L. Beitle

1946

	4/8	1940	•
LINE 2 (Cont'd.)			Feet
Reference mark; 91 ft W. of tablet; 47 ft N. and 29 ft W. of junction of on SE. side of 10-in. pine tree; spike	T-rd. H.; in b	oasé .	217.78
U.E. Raeford; 2.1 mi E. of RR. station, along U. S. Highway 15A, thence macadam and dirt rds.; 4.0 mi W. of Rockfish along dirt rd.; 0.17 mi E. 32 ft S. and 14 ft W. of I-junction of lane S.; in base on NE. side of spike	of T-rd. N.;	•	220.29
Rockfish, 2.8 mi W. of; about 0.5 mi E. of bridge over Puppy Creek; 6 ft junction of drive vay to church; in concrete post; standard tablet stamp (Reported not found, 1971)			211.427
Reference mark; 93 ft SE. of tablet; 47 ft S. and 29 ft E. of junction of in root on NW. side of 6-in. oak tree; copper nail and washer	fird. S. to chu	arch;	209.94
U.E., Rockfish; 1.4 mi W. of RR. station, along dirt rd.; 57 ft S. of cer of NW. corner of frame house; in root on NE. side of 30-in. oak tree; to copper nail and washer			228.99
Rockfish; at Community House; 14 ft S. of center of rd.; 5 ft E. of telepcenter of ditch; in E. corner of cultivated field; in concrete post pro-above ground; USED standard disk stamped "3 TT A 9576"			217.000
Rockfish; on Aberdeen and Rockfish Railroad; 222 ft W. of center of rd. o center of graded rd.; 6 ft S. of large oak tree; in concrete post; Nort Survey standard disk stamped "NC 351"			217.532
U.E., Rockfish Railroad Station, 0.3 mi SE. of, thence 0.7 mi NE. along of wooden bridge over Stewart Creek; at Cumberland-Noke County line; 34 ft in root on N. side of 10-in. oak tree; copper nail and washer			182.65
Rockfish, 1.6 mi NE. of, thence 0.4 mi SE. along graded rd.; 1.4 mi NW. o powerline; 43 ft S. and 13 ft E. of junction of farm rd. S.; in concret stamped "TT 26 FLS 1946 219" (Post out of ground, 1971)			218.904
Reference mark; 28 ft NE. of tablet; 25 ft SE. and 21 ft NE. of junction center of field rd. NE.; in concrete post; copper nail and washer	of lane S.; 17	ft SE. of	218.49
U.E., Rockfish, 3.1 mi NE. of; 0.9 mi SW. of bridge over Little Rockfish 119 ft W. of junction of I-rd.; in root on SE. side of 36-in. oak tree; washer			207.76
	•	•	roleto

# W. S. Monk, 1949; Book AV 84

Duffies, 0.8 mi SE. of, thence 0.4 mi N.; 1.2 mi SW. of Mount Elim Church; 20 ft W. of rd.; 75 ft NW. of SM. corner of residence; in frontyord; 35 ft W. of 34-in. oak tree; in concrete post; standard tablet stamped "53 WSM 1949 225"

LINE 3.

LINE 3 (Cont'd.)	Feet
Reference mark; 35 ft E. of tablet; in root on W. side of 34—in. oak tree; copper nail and washer	224.72
UvE., Mount Elim School, 0.5 mi SM. of; 50 ft N. of rd.; 50 ft SM. of SM. corner of residence; in root on SM. side of 50-in. sycamore tree; copper nail and washer	232.02
U.E., Mount Elim School; 35 ft E. of small stream; 30 ft S. of and 1 ft lower than rd.; in root on NE. side of 14-in. poplar tree; copper nail and washer	207.76
Mount Elim School, 0.8 mi NE. of; 0.7 mi W. of Antioch; 50 ft S. and 275 ft W. of junction of Antioch-Wagram Road and rd. SW.; centered under high-tension line tower; in concrete post; standard tablet stamped "54 WSM 1949 231" (Tablet missing, 1971)	231.306
U.E., Antioch; 270 ft SW. of junction of Antioch-Raeford Road and rd. NE.; at concrete bridge over Raft Creek; on SW. concrete abutment; chiseled square	201.03
Antioch, 1.1 mi N. of; 25 ft E. of Antioch-Raeford Road; in concrete post; NGS standard azimuth mark disk stamped "HODGIN 1949"	227.688
Antioch, 1.6 mi N. of; 110 ft N. and 35 ft W. of junction of Antioch-Raeford Road and rd. NM.; in concrete post; NGS standard triangulation station disk stamped "HOOGIN 1949"	225.726
Reference mark No. 1; 80 ft NE. of station; NGS standard reference mark disk stamped "HODGIN NO 1 1949"	226.449
Reference mark No. 2; 100 ft W. of station; NGS standard reference mark disk stamped "HODGIN NO 2 1949" (Reported destroyed, 1971)	225.858
U.E., Antioch, 2.2 mi N. of; 430 ft N. and 55 ft W. of intersection of hwy. and EW. field rd.; in root on NE. side of 20-in. twin maple trees; copper nail and washer	231.10
Antioch, 3.0 mi N. of; 0.18 mi S. and 15 ft E. of crossroads; in S. end of concrete headwall of culvert; standard tablet stamped "55 WSM 1949 225" (Reported not found, 1971)	225.545
Reference mark; 0.13 mi W. of tablet; 300 ft S. and 15 ft E. of crossroads; in root on SW. side of 32—in. oak tree; copper nail and washer	234 <b>.2</b> 3
Raeford; 2.1 mi S. of station, along Antioch-Raeford Road; 15 ft E. of huy.; in S. end of concrete headwall of culvert over small stream; standard tablet stamped "56 WSM 1949 237"	237.025
U.E., Raeford; 1.2 mi S. of station, along Antioch-Raeford Road; 15 ft E. of hwy.; 2 ft lower than rd.; in center of concrete headwall of culvert over small stream; chiseled square	240.46
."Z 74 1935" (NGS)	258.293
LINE 4.	

W. S. Monk, 1949; Book AV 84

NGVD 29 Elevations

"Z 74 1935" (NGS) (Also in line 3)

b		
		RAEFORD
ook	W	84

#### NORTH CAROLINA

W. S. Monk

LINE 4 (Contid.)

1949

U.E., Raeford First Presbyterian Church, 1.1 mi SM. of, along U. S. Highway 15A; 220 ft S. of residence standing on W. side of hwy.; 15 ft W. of hwy.; in center on concrete headwall of culvert; chiseled square

246.65

Feet

### LINE 5.

W. S. Monk, 1949; Book AV 84

Wakulla, 1.5 mi NE. of, along Red Springs-Wakulla Road, thence 0.8 mi N.; 30 ft W. of rd.; 4565 20 ft SE. of SE. corner of residence; in concrete post projecting 0.2 ft.; standard tabletor found stamped "69 WSM 1949 213" PROB DEST RESIDENCE GONE, AREA WOW A PLOWED FIELD ALSO RD. WAS BEEN IMPROVED & DITCHED

Reference mark; 200 ft SE. of tablet; in root on S. side of 14-in. oak tree; copper nail and washer

213.86

# LINE 6.

W. S. Monk, 1949; Book AV 84

U.E., Wakulla, 3.1 mi SE. of, along Pembroke-Wakulla Road; 90 ft S. and 50 ft W. of junction of Pembroke Road and rd. W.; 110 ft W. of SW. corner of residence; in root on SE. side of 20-in. pine tree; copper nail and washer

194.55

## LINE 7.

R. E. Welty, 1951; Book AV 274

Parkton; 260 ft NE. of RR. station; 63 ft N. and 15 ft E. and about 2 ft lover than intersection of blacktop street and Atlantic Coast Line Railroad; 19 ft NM. of W. rail of side track; 3 ft N. of concrete signal box; in concrete post; standard tablet stamped "56 REW 1951 186"

186.202

Reference mark; 70 ft SW. of tablet; on W. corner of concrete base of signal light; chiseled square

188,58

Parkton, 2.1 mi S. of, along blacktop rd.; 250 ft S. and about 3 ft higher than junction of Y-rd. SE.; 28 ft W. of E. branch of center of Y-rd.; in concrete post; standard tablet stamped "57 REW 1951 164" (Reported not found, 1971)

164.318

### LINE 8.

J. R. Rigby, 1946; Book V 262 a

There are no permanent marks on this line in this quadrangle.

NGVD 29 Elevations

## LINE 9.

H. L. Zohn, 1971; Book AV 1614

62 U.E., in junction of County Roads 1006 and 1762; copper nail and washer, 2 2.39 painted "CL 169.5"

RAEFORD NORTH CAROLINA H. L. Zohn Book AV 1614 1971 LINE 9 (Cont'd.) Feet 2 63 3.28 St. Pauls, 1.9 mi W. of, along County Road 1006 from junction of U. S. Highway 301, thence 0.7 mi S. along County Road 1762, thence 0.2 mi SW. along County Road 1318; 0.5 ft NV. of witness post; 35 ft SE. and about 1 ft higher than junction of County Roads 1318 and 1784; in concrete post projecting 0.2 ft.; standard tablet stamped "108 HLZ 1971 177", painted "BM 177.1" 177.057 64 U.E., rd. at fence SE. (PP. 4-233 C) 2 **3.5**1 175.26 65 4.31 U.E., in centerline of County Road 1318 at drive N.; copper nail and washer, painted "CL 176.3" 176.27 2 5.22 St. Pauls, 1.9 mi W. of, along County Road 1006 from junction of U. S. 66 Highway 301, thence 0.7 mi S. along County Road 1762, thence 2.3 mi SW. along County Road 1318; 0.5 ft S. of witness post; 46 ft N. and 21 ft W. of, and about 1 ft lower than junction of County Roads 1318 and 1763; in concrete post projecting 0.2 ft.; standard tablet stamped "109 HLZ 1971 188", painted "BM 188.3" 183.306 2 67 5.90 U.E., in junction of County Roads 1318 and 1752; copper nail and washer, painted "CL 178.2" 178.22 6.41 U.E., in centerline of County Road 1318 at dirt rd. NEW.; copper nail and 68 washer, painted "CL 181.6" 181.54 69 7.09 U.E., in junction of County Roads 1001 and 1318; copper nail and washer, 168.27 painted "CL 168.3" 2 . 70 7.44 St. Pauls, 1.9 mi W. of, along County Road 1006 from junction of U. S. Highway 301, thence 0.7 mi S. along County Road 1762, thence 4.6 mi SW. along County Road 1318; at 160-ft bridge over Big Raft Swamp; on E. end of N. concrete guardrail base; standard tablet stamped "110 HLZ 1971 155", painted "BM 154.8" 154.821 NGVD 29 WL = 149 ftElevations 2 70 7.44 (PP. 6-78 C) 154.13 U.E., in junction of County Roads 1318 and 1507; copper nail and washer, 2 71 8.05 painted "CL 171.5" 171.44 8.94 2 72 Philadelphus, 0.3 mi N. of, along State Highway 72 from junction of County Road 1318, thence 3.0 mi E. along County Road 1507; 235 ft SW. of RR. crossing; 1.5 ft ME. of milepost 234; 15.5 ft SE. of SE. rail; 1 ft MW. of witness post; in concrete post projecting 0.2 ft.; standard tablet stamped

"111 HLZ 1971 183", painted "BM 183.5"

1	1	ŀ	
U		,	

RAEFORD

MORTH CAROLINA

H. L. Zohn

Book A	V 1614	NORTH CAROLINA	NGVD 29 Elevations	1971	
LINE 9	(Cont'd.)	• .	AdON8	19/1	Feet
2 73	9.62	U.E., in centerline of County Road 1507 at dirt and washer, painted "CL 185.2" $$	rd. N.; cooper na	<b>i</b> 1	185.18
2 74	10.02	U.E., in junction of State Highway 211 and Coun and washer, painted "CL 181.4" $$	ty Road 1507; copp	er nail	181.35
2 75	10.42	Philadelphus, 0.3 mi W. of, along State Highway County Road 1318, thence 1.5 mi E. along County witness post; 58 ft S. and 13 ft W. of, and abo of County Roads 1507 and 1510; in concrete post tablet stamped "112 HLZ 1971 184", painted "BM	Road 1507; I ft N ut 3 ft nigher tha projecting 0.5 ft	. of n junction	183.908
2 76	11.03	U.E., in junction of County Roads 1507 and 1500 painted "CL 185.3"	; copper nail and	washer,	185.25
2 77	11.96	U.E., in junction of State Highway 72 and Count and washer, painted "CL 173.8"	y Road 150 <b>7;</b> coppe	r nail	173.75
2 78	12.23	Reference mark No. 1; 107 ft NE. of station; 13 school; 23 ft W. of dirt lane; in concrete post standard reference mark disk stamped "PHILADELP	flush with ground		187.512
2 79	12.25	Philadelphus High School, 164 ft S. of S. end; 21 ft NE. of white witness post; in concrete po NGS standard triangulation station disk stamped	st flush with grou	nd;	187.878
2 80	12.27	Reference mark No. 2; 118 ft NM. of station; 90 ft S. of SM. corner of school; in concrete post standard reference mark disk stamped "PHILADELP	flush with ground		187.782
3 3	13.07	Philadelphus, 0.9 mi S.M. of, along County Road Road 1318; 2 ft M. of power pole; 38 ft S. and County Roads 1346 and 1582; 0.5 ft M. of witnes projecting 0.2 ft.; standard tablet stamped "11 "BM 189.9"	about level with j s post; in concret	unction of e post	169.371
3 4	13.75	U.E., in centerline of County Road 1346 at driv painted "CL 192.9"	e NW.; copper nail	and washer,	192.82
3 5	14.39	Red Springs, 5.1 mi S. of, along State Highway of gravel rd.; 17 ft W. of white witness post; 0.3 ft.; NGS standard triangulation station dis	in concrete post p	rojecting	191.276
		∑Jogs into Pembroke quadra	ngle/		

197.14

U.E., in junction of County Roads 1345 and 1342; copper nail and washer, painted "CL 197.2" 15.00

Roy	nk AV	RAEFORD 1614	NORTH CAROLINA		H. L. Zohn	
		(Cont'd.)	-		1971	Feet
3	7	15.97	U.E., in junction of County Roads 1345 and 1344; copper masher, painted "CL 198.1"	nail and		197.98
3	9	16.35	Philadelphus, 3.9 mi S.M. of, along County Road 1346 from County Road 1318, thence 1.2 mi NM. along County Road 134 power pole; 47 ft NNM. of, and about 0.5 ft lower than ju County Roads 1340 and 1345; 0.5 ft NE. of witness post; i projecting 0.5 ft.; standard tablet stamped "114 HLZ 1971" MM 195.9"	40; 2 ft H. Unction of in concrete	of post	195.872
			LINE 10.			
н.	L. Z	ohn, 1971;	Book AV 1614	•		
3	16	0.00	"112 HLZ 1971 184" (Described in line 9)			183.908
3	16	0.68	U.E., in junction of County Roads 1500 and 1510; copper repainted "CL 182.5"	nail and wa	sher,	182.49
			LINE 11.			
н.	L. Z	ohn, 1971;	Book AV 1614		•	
3	36	0.00	"U.E., copper nail and washer" (Described in line 9)			168.27
3	36	0.45		IGVD 29		158.90
3	37	0.90	U.E., Y-rd (PP. 6-77 C)	levations		175.07
3	38	1.34	U.E., rd. at drain S./. (PP. 6-76 A)			183.43
3	39	1.48	Shannon, 4.5 mi SE. of, along County Road 1001 from junct Highway 71; at 180-ft bridge over railroad; in NW. end of base; standard tablet stamped 1126 HEZ 1971 1981, painted	f NE. guard	rail	198,356
3	40	2.29	U.E., in centerline of County Road 1001 at dirt rd. NE.; and washer, painted "CL 187.2."	copper mai	l	187.17
3	41	3.09	Shannon, 2.7 mi SE. of, along County Road 1001 from junct Highway 71; 99 ft S. of, and 2 ft higher than centerline Road 1006; 65 ft NE. of, and 2 ft higher than centerline 1001; 0.5 ft SE. of witness post; in concrete post project standard tablet stamped "127 NEZ 1971 194", painted "BM 1	of County of County i cting 0.2 fi	Road	193.749

Book AV 1614

RAEFORD

NORTH CAROLINA

NGVD 29 Elevations

H. L. Zohn

10

	1971	
LINE 11 (Cont'd		Foet
3 42 3.77	U.E., centerline of crossroads, painted "CL 194.2" (PP. 6-48 C)	194.15
3 43 4.34	Shannon, 1.3 mi SSE. of, along County Road 1001 from junction of State Highway 71; 56 ft E. of, and 0.5 ft higher than junction of County Road 1001 and dirt rd. NE.; 0.5 ft W. of witness post; in concrete post projecting 0.2 ft.; standard tablet stamped "128 HLZ 1971 197", painted "BM 196.9"	196.885
3 44 4.98	U.E., in centerline of County Road 1001 at dirt rd. E.; copper nail and washer, painted "CL 198.7"	198.64
3 45 5.53	U.E., Shannon; in junction of State Highway 71 and County Road 1001; copper nail and washer, painted "CL 200.6"	200.57
3 46 6.55	Shannon, 1.1 mi N. of, along County Road 1001 from junction of State Highway 71; 50 ft ESE. of, and level with junction of County Roads 1001 and 1702; 0.5 ft W. of witness post; in concrete post projecting 0.2 ft.; standard tablet stamped "129 HLZ 1971 217", painted "BN 217.3"	217.522
3 47 7.33	U.E., in junction of County Roads 1001 and 1446; copper nail and washer, painted "CL 211.6"	211.62
3 48 7.73°	Shannon, 2.3 mi NUM. of, along County Road 1001 from junction of State Highway 71; 85 ft N. and about level with junction of County Roads 1001 and 1436; 0.5 ft S. of witness post; in concrete post projecting 0.2 ft.; standard tablet stamped "130 HLZ 1971 208", painted "BH 208.4"	(208.427)
3 49 8.13	U.E., rd. at drive NM. (PP. 5-119 A)	218.71
3 50 8.71	U.E., in junction of County Roads 1448 and 1436; copper nail and washer, painted "CL 213.5"	213.43
3 51 9.19	Antioch, 0.7 mi NE. of, along County Road 1005 from junction of State Highway 211, thence 2.0 mi SE. along County Road 1448; 1.5 ft MV. of power pole; 95 ft W. and about 1 ft higher than junction of County Road 1448 and dirt rd. NE.; 0.5 ft NE. of witness post; in concrete post projecting 0.2 ft.; standard tablet stamped "131 NLZ 1971 205", painted "BM 205.5"	205.474
3 52 9.76	U.E., in centerline of County Road 1448 at dirt rd. H.; copper nail and washer, painted "CL 217.3"	217.23
3 53 10.50	Antioch, 0.7 mi NE. of, along County Road 1105 from junction of State Highway 211, thence 0.6 mi SE. along County Road 1448; 2 ft E. of power pole; 51 ft NV. of, and 0.4 ft lower than junction of County Road 1448 and dirt rd. NE.; 0.5 ft S. of witness post; in concrete post projecting 0.1 ft.; standard tablet stamped "132 HLZ 1971 223", painted "BM 223.3"	223.286

Oundarrach, 2.4 mi SE. and E. of, along State Highway 20 from junction of County Road 1105; 1 ft SM. of fence; 54 ft N. and 54 ft E. of, and about level with junction of State Highway 20 and County Road 1436; 1.5 ft S. of witness post; in concrete post projecting 0.2 ft.; standard

tablet stamped "134 HLZ 1971 214", painted "3H 213.5"

washer, painted "CL 219.6"

U.E., in junction of County Roads 1436 and 1434; copper nail and

3 68

3 69

3.34

3.69

NGVD 29 Elevations 1213.473

RAEFORD Book AV 1614

Bo	ok AV	1614	·	
LI	IIE 12	(Cont'd.)	. 1971	<u>Feet</u>
3	. <b>7</b> 0	4.36	U.E., in centerline of County Road 1436 at centerline of drain crossing; copper nail and washer, painted "CL 209.6"	209.49
		•	WL = 204 ft	
3	71	4.78	Dundarrach, 2.4 mi SE. and E. of, along State Highway 20 from junction of County Road 1105, thence 1.6 mi NE. along County Road 1436; 120 ft NW. of, and level with junction of County Roads 1435 and 1436; 5 ft S. of witness sign on tree; in concrete post projecting 0.2 ft.; standard tablet stamped "135 HLZ 1971 217", painted "BN 216.9"	216.823
3	72	5•35	U.E., in junction of County Roads 1105 and 1435; copper nail and washer, painted "CL 214.1"	214.04
3	.73	5•92	U.E., in junction of County Roads 1003 and 1435; copper nail and washer, painted "CL 212.3"	212.25
3	74	6.72	"V 74 1935" (NGS)	224.481
3	75	7.15	"U.E., rd. at drain, painted "CL 203.8" (PP. 6-56 C)	203.69
			₩L == 195 ft	
3	76	8.06	U.E., in junction of County Roads 1432 and 1427; copper nail and washer, painted "EL 149.4"	149.24
3	77	8.50	nu 74 1935" (IISS)	174.258
			LINE 13.	
Н.	L. Zo	hn, 1971;	Book AV 1614	
Ļ	3	0.00	"133 HLZ 1971 193" (Described in line 12)	192.623
4	3	1.14	U.E., in centerline of County Road 1704 at dirt rd. SSW.; copper nail and washer, painted "CL 208.7"	208.74
4	Ļ	2.12	Lumber Bridge; 0.9 mi SW. of post office, along State Highway 71, thence 0.4 mi RW. along County Road 1705; 63 ft S. and about level with junction of County Roads 1704 and 1705; 2 ft W. of witness post; in concrete post projecting 0.2 ft.; standard tablet stamped "136 HLZ 1971 201", painted "BM 200.7"	200.754
4	5	2.57	U.E., in junction of State Highway 71 and County Road 1751; copper nail and washer, painted "CL 197.5"	197.27

RAEFORD Book AV 1614

		•	
LINE	13 (Cont*d.	.)	Feet
.4 6	3.37	Lumber Bridge; in W. angle of intersection of State Highways 71 and 20; 234 ft SW. of intersection; 74 ft RM. of center of Highway 71; 47 ft RM. of NW. corner of small concrete building; in concrete post projecting 0.2 ft.; NGS standard triangulation station disk stamped "LUMBER BRIDGE 1949"	192.632
4 7	3.79	U.E., Y-rd. SE. (PP. 1-301 A)	191.41
4 8	3.98	U.E., in centerline of 30-ft bridge over small stream; copper mail and washer, painted "CL 181.7"	181.73
		WL = 175 ft	
4 9	4.66	U.E., in centerline of State Highway 71 at drain crossing; copper nail and washer, painted "CL 188.6"	183.65
		WL == 182 ft	
4 10	5.23	Parkton, 1.5 mi SW. of; Azimuth mark; 54 ft W. of center of driveway; 36 ft S. of center of State Highway 71; in concrete post projecting 0.5 ft.; HGS standard azimuth mark disk stamped "PARKTON 1949"	191.128
4 11	5.56	U.E., rd. at drain (PP. 4-226 C)	187.28
		WL == 181 ft	
4 12	5•90	Reference mark No. 1; 62 ft N. of NW. leg of lookout tower; in concrete post projecting 0.5 ft.; NGS standard reference mark disk stamped "PARKION NO 1 1949"	185.810
4 13	5.92	Parkton, 0.8 mi SM. of; 15 mi SM. of Fayetteville; 107 ft W. of center of State Highway 71; 51.83 ft SM. of center of base of Parkton Lookout Tower; 42 ft SM. of WM. leg of lookout tower; in concrete post flush with ground; NGS standard triangulation station disk stamped "PARKTON 1949"	186.068
. 4 14	5.93	Reference mark No. 2; 55 ft SE. of SE. leg of lookout tower; 45 ft N. of center of hwy.; in concrete post flush with ground; NGS standard reference mark disk stamped "PARKTON NO 2 1949"	185,585
4 19	6.67	"56 REW 1971 186" (Described in line 7)	185,202