THIRD-ORDER LEVELING WATER OF 1929

3

UNITED STAYES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

35-060-22
HORWOOD OWASPANGLE
MORTH CARCLINA
M3500-W6000/15
DIAGRAM HI 17-2
CHARLOTTE

Anson, Montgomery, Richmond and Stanly Counties


Final adjustment of 1975

Edition of 7/2/75

PR: WSW/mic

NGVD 29 Elevations

ALBEMARLE (114)



(.o.2 881-3.04)

market and contact to the contact and

A. Quadrangle 350802

START TELO

(78)

ELLERGE (76)

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.	MARK (USGS)	PAGE NO.
35 WSM 1954 243	3	249 HLZ 1969	.15
36 WSM 1954 295	3	250 HLZ 1969	5
37 WSM 1954 268	3,4	251 HLZ 1969	6
38 WSM 1954 194	3	252 HLZ 1969	6
39 WSM 1954 247	3	253 HLZ 1969	ć
46 WSM 1954 221	4	254 HLZ 1969	. 6
62 WSN 1954 419	. 3	261 HLZ 1969	· Ġ
63 WSM 1954 402	4	262 HLZ 1969	6.
64 WSM 1954 325	4		
65 WSH 1954 270	4	NGS	
1 WDL 1955 284	5	histories	
44 WOL 1955 479		\$ 50 1933	6
46 WDL 1955 488	. 5	U 50 1933	3
246 HLZ 1969	5	MT GILEAD 1948	4,4
247 HLZ 1969	5	MT GILEAD NO 1 1948	4
248 HLZ 1969	5,6	MT GILEAD NO 2 1948	4,4

NGVD 29 Elevations

1954

EINE 1.	Feet
By W. S. Monk, 1954; Book AV 390	
Lilesville, 0.5 mi W. of depot, thence 3.1 mi N., thence 1.3 mi NW.; 14.3 mi S., thence 0.8 mi E Mt. Gilead; at NE. end of bridge crossing Cedar Creek; 17 ft E. of centerline of rd.; in concrabutment; standard tablet stamped "35 WSM 1954 243"	
Reference mark; 15 ft SE. of tablet; in root on W. side of 12 in. maple tree; copper mail and wa	sher 243.48
U.E., Mt. Gilead, 13.0 mi S. of; at drain crossing; 16 ft E. of State Highway 109; on center of concrete headwall of culvert; chiseled cross	257.06
Mt. Gilead, 12.0 mi S. of; 300 ft S. of school; 175 ft N. and 42 ft W. of, and 2.0 ft higher tha field rd. W.; 2.5 ft E. of power pole; in concrete post; standard tablet stamped "36 WSM 1954	
Reference mark; 200 ft N. of tablet; 25 ft W. of centerline of hwy.; on concrete headwall of cul chiseled cross	vert; 289.23
Mt. Gilead, 10.5 mi S. of; 90 ft S. and 38 ft E. of, and 5.0 ft higher than crossroads; in concr post; standard tablet stamped "37 WSM 1954 268"	rete 267•324
Reference mark; 340 ft S. of tablet; 20 ft E. of State Highway 109; on concrete headwall of culv chiseled cross	ert; 260 , 52
Mt. Gilcad, 10.9 mi S. of, thence 0.6 mi W., thence 1.4 mi SW.; 3.1 mi N., thence 0.2 mi E., the 3.1 mi NE. of Pinkston; in SE. concrete abutment of wooden bridge crossing small stream; stand tablet stamped "38 WSM 1954 194"	
Reference mark, 1140 ft E. of tablet; 26 ft S. of centerline of rd.; in root on N. side of 10 in tree; copper nail and washer	oak 202.16
Pinkston, 3.1 mi NE. of; 35 ft N. and 90 ft E. of, and 3.0 ft lower than crossroads; in concrete standard tablet stamped "39 WS4 1954 247"	post; 247.035
Reference mark; 500 ft W. of tablet; 90 ft N. of centerline of rd.; in face on N. side of 6 in. p tree; rail spike	ersimmon 255•71
"U 50 1933" (NGS)	290.357
LINE 2.	
By W. S. Monk, 1954; Book AV 390	
Mt. Gilead, 850 ft W. of depot; 10 ft S. of, and 5 ft higher than S. rail; in concrete pier for everhead bridge; standard tablet stamped "62 WSM 1954 419"	419.152
Reference mark; 25 ft S. of, and 20 ft higher than tablet; on SE concrete abutment of overhead bridge; chiseled cross	439.69

	evations	·
LINE 2 (Cont'd)		Feet
Mt. Gilead, 0.3 mi NW. of center of town; on property owned by United Mills; 194 section of State Highways 73 and 109; 145 ft N. of NE. ocrner of United Mills be of centerline of State Highway 73; 57 ft NE. of center of Mt. Gilead Municipal SE. of center of entrance drive; NGS standard triangulation disk stamped "MT GI	uilding; 97 ft SW. Water Tank; 52 ft	433•278
Mt. Gilead, 0.3 mi NW. of center of town; on property owned by United Mills; 19 f entrance drive; 30 ft SW. of centerline of State Highway 73; in drill hole in N retaining wall; NGS standard reference disk stamped "MT GILEAD NO 2 1948"		433.824
Mt. Gilead, 1.6 mi S. of; 25 ft E. of, and 4.0 ft lower than State Highway 109; 3 level with junction of rd. W.; in center of concrete headwall of culvert; stand "63 WSM 1954 402"		401.759
Reference mark; 200 ft S. of tablet; 60 ft E. of centerline of hwy.; in face on S oak tree; rail spike	W. side of 10 in.	408.88
U.E., Mt. Gilead, 3.2 mi S. of; at drain crossing; 20 ft E. of State Highway 109; concrete headwall of culvert; chiseled cross	on S. end of	318.21
Mt. Gilead, 3.8 mi S. of; 190 ft S. and 20 ft W. of, and 3.0 ft lower than junction 109 and I-rd. W.; in center of concrete headwall of culvert; standard tablet stim64 WSM 1954 325"	• -	324.588
Reference mark; 320 ft N. of tablet; 25 ft W. of centerline of hwy.; 100 ft N. of concrete headwall of culvert; chiseled cross	store; on N. end of	341.15
Mt. Gilead, 5.5 mi S. of; 60 ft S. and 30 ft W. of, and 1.0 ft lower than junction 109 and rd. SW.; 4.5 ft S. of telephone pole; in concrete post; standard tablet "65 WSM 1954 270"		269.644
Reference mark; 500 ft N. of tablet; 20 ft E. of hwy.; on concrete headwall of cu cross	lvert; chiseled	266.93
LINE 3.	•	
By W. S. Monk, 1954; Book AV 390		
"37 WSM 1954 268" (Described in line 1)		267.324
U.E., 15 ft E. and 5 ft lower than State Highway 109; on NE. concrete abutment of bridge; chiseled cross	f steel girder	215.27
Mt. Gilead, 8.2 mi S. of; 470 ft S. and 25 ft E. of, and 3 ft lower than I-rd. W. concrete headwall of culvert; standard tablet stamped "45 WSM 1954 221"	.; in center of E.	221.284
Reference mark; 45 ft W. of tablet; on M. end of concrete culvert; chiseled cross		221.31
By W. D. Leech, 1955-56; Book AV 458		
'MY GILEAD 1948" (Described in line 2)		433.278
"AT SILEAD NO 2 1948" (Describer in line 2)	om 1 ** 1	433.624
Reference wark No. 1; 85 ft E. of station; 29 ft SW. of centerline of State High in drill hole at SE. end of red brick retaining wall; NGS standard reference ma MAY GILEAD NO 1 1948"	rry 73; set flush ark disk stamped	432.483

tablet stamped "250 HLZ 1969"

263,686

้หย่	9.V00	D QUADRA	NGLE 77 NORTH CAROLINA	35-080-22
			NGVD 29	6
LI	NE 6	(Cont'd) Elevations	Feet
3	73	13.51	Burnsville, 2.2 mi NE. of junction of State Highway 742 and County Road 1610, along Road 1610, thence 0.5 mi SE. along County Road 1600, thence 1.5 mi E. along County Road 1612; at 200 ft bridge over Lanes Creek; in NE. end of NW. backwall; standard tablet stamped "251 HLZ 1969"	253-811
3	75	14.99	Ansonville, 2.0 mi W. of United Methodist Church, along County Road 1418, thence 1.1 mi NNW. along County Road 1618, thence 1.0 mi NNW. along County Road 1619; at Gulf Service Station; in W. end of concrete base for gas pumps; standard tablet stamped "252 HLZ 1969"	403.958
3	77	16.62	Ansonville, 2.0 mi W. of United Methodist Church, along County Road 1418, thence 0.3 mi N. along County Road 1618; at lookout tower; in concrete base for steps leading up tower; standard tablet stamped "253 HLZ 1969"	429.829
4	5	17.69	Ansonville, 1.2 mi W. of United Methodist Church, along County Road 1418; at Pleasant Hill Church; 15 ft W. of SW. corner of church; in SE. corner of concrete base for bell; standard tablet stamped "254 HLZ 1969"	331.301
4	7	18.70	"S 50 1933" (NGS)	306.184
			LINE 7.	
Ву	H.	L. Zohn,	Jr., 1969; Book AV 1558	
4	32 .	8.83	"248 HLZ 1969" (Described in line ?)	497.038
			LINE 8.	
Ву	н.	L. Zohn,	Jr., 1969; Book AV 1558	
	42	1.01	Burnsville, 2.2 mi NE. of junction of State Highway 742 and County Road 1610, along Road 1610, thence 1.05 mi NUW. along County Road 1600; 37 ft NE. of, and 2.0 ft lower than junction of County Roads 1600 and 1607; 0.5 ft W. of witness sign; in concrete post projecting 4 in.; standard tablet stamped "261 HLZ 1969"	342 . 492
4	44	1.95	Burnsville, 2.2 mi NE. of junction of State Highway 742 and County Road 1610, along Road 1610, thence 2.0 mi NW. along County Road 1600; at 130 ft bridge over Richardson Creek; in NE. end of NW. backwall; standard tablet stamped "262 HLZ 1969"	260.343

PAGE NO.

MARK (USGS)

242 HLZ 1969 243 HLZ 1969 244 HLZ 1969 245 HLZ 1969 246 HLZ 1969 247 HLZ 1969 248 HLZ 1969


NORWOOD QUADRANGLE WITH OVEREDGE

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY THIRD-ORDER LEVELING

UNADJUSTED FIELD ELEVATIONS

SEA LEVEL DATUM OF 1929 Edition of 4/22/70

Counties: Anson, Montgomery, Richmond, and Stanly



WSM 1954 WSM 1955 WSM 1955 16 17 17 18 18 20 20 21 251 HLZ 1969 252 HLZ 253 HLZ 254 HLZ 1969 1969 1969 566 261 HLZ 262 HLZ 263 HLZ 1969 6,9 8 10 11 12 12 13 14 14 15 15 USC&GS J 50 R 50 R 50 S 50 U 50 F 51 W 72 11 18 18 18 5 13 6 7,9 7,9 44 45 W1 46 WDL 47 WDL 1 242 HLZ 1 243 HLZ 1 14 HLZ HLZ HLZ 1933 1933 1933 1933 1933 1934

16,19

INDEX OF PERMANENT MARKS

PAGE NO.

MARK (USGS)

MT GILEAD 1948 MT GILEAD NO 1 MT GILEAD NO 2

NGVD 29 Elevations

3 NORWOOD Bk. AV 390 a 4/21/70 els

NORTH CAROLINA

W. S. Monk

1954

LINE 1.

FROM ROCKINGHAM QUADRANGLE ALONG ROADS GENERALLY NORTH THENCE SOUTHWEST TO POINT ABOUT 4.2 MILES SOUTHEAST OF ANSONVILLE (By W. S. Monk, 1954; Book AV 390 a)

Lilesville, 0.5 mi W. of depot, thence 2.1 mi N.; 90 ft N. and 38 ft W. of, and 3.0 ft higher than junction of rd. W.; 2 ft S. of power pole; in concrete post; standard tablet stamped "34 WSM 1954 374"

Reference mark; 920 ft S. of tablet; 20 ft W. of centerline of rd.; in root on W. side of 16-in. pine tree;

copper nail and washer Lilesville, 0.5 mi W. of depot, thence 3.1 mi N., thence

1.3 mi NW.; 14.3 mi S., thence 0.8 mi E. of Mt. Gilead; at NE. end of bridge crossing Cedar Creek; 17 ft E. of centerline of rd.; in concrete abutment; standard tablet stamped "35 WSM 1954 243"

Reference mark; 15 ft SE. of tablet; in root on W. side of 12-in. maple tree; copper nail and washer

U.E., Mt. Gilead, 13.0 mi S. of; at drain crossing; 16 ft E. of State Highway 109; on center of concrete headwall of culvert; chiseled cross

Mt. Gilead, 12.0 mi S. of; 300 ft S. of school; 175 ft N. and 42 ft W. of, and 2.0 ft higher than field rd. W.; 2.5 ft E. of power pole; in concrete post; standard tablet stamped "36 WSM 1954 295"

NORWOOD Bk. AV 390 a 4/21/70 els

NORTH CAROLINA

W. S. Monk 1954

289.23

267.324

260.52

268.32

193.721

LINE 1 (Cont'd.)

Reference mark; 200 ft N. of tablet; 25 ft W. of centerline of hwy.; on concrete headwall of culvert; chiseled cross

Mt. Gilead, 10.5 mi S. of; 90 ft S. and 38 ft E. of, and 5.0 ft higher than crossroads; in concrete post; standard tablet stamped "37 WSM 1954 268"

Reference mark; 340 ft S. of tablet; 20 ft E. of State Highway 109; on concrete headwall of culvert; chiseled

cross U.E., Mt. Gilead, 10.9 mi S. of, thence 0.9 mi SW.; 90 ft N. and 55 ft E. of, and 2.0 ft lower than Y-rd. junction; in root on S. side of 12-in. gum tree; copper nail and

Mt. Gilead, 10.9 mi S. of, thence 0.6 mi W., thence 1.4 mi SW.; 3.1 mi N., thence O.2 mi E., thence 3.1 mi NE. of Pinkston; in SE. concrete abutment of wooden bridge crossing small stream; standard tablet stamped

"38 WSM 1954 194" Reference mark; 1140 ft E. of tablet; 26 ft S. of center-

line of rd.; in root on N. side of 10-in. oak tree; 202.16 copper nail and washer

243.48

243.343

373.646

352.36

257.06

295,125

5 NORWOOD NORTH CAROLINA W. S. Monk Bk. AV 390 a 4/21/70 els LINE 1 (Cont'd.)	6 NORWOOD NORTH CAROLINA W. S. Monk Bk. AV 390 a 4/21/70 els LINE 3 (Cont'd.)
Pinkston, 3.1 mi NE. of; 35 ft N. and 90 ft E. of, and	Mt. Gilead, 8.2 mi S. of; 470 ft S. and 25 ft E. of, and
3.0 ft lower than crossroads; in concrete post; standard	3.0 ft lower than T-rd. W.; in center of E. concrete
tablet stamped "39 WSM 1954 247" 247.035	headwall of culvert; standard tablet stamped
Reference mark; 500 ft W. of tablet; 90 ft N. of center-	M46 WSM 1954 221" 221.284
line of rd.; in face on N. side of 6-in. persimmon tree; rail spike 255.71	Reference mark; 45 ft W. of tablet; on N. end of concrete culvert; chiseled cross
U.E., Pinkston, 3.1 mi NE. of, thence 0.7 mi W.; 25 ft S.	Mangum; 20 ft S. and 130 ft E. of, and 4.0 ft lower than
of, and level with Y-rd. fork; in root on N. side of	crossroads; 2.5 ft N. of power pole; in concrete post;
30-in. pine tree; nail and washer 267.96	"standard tablet stamped "47 WSM 1954 286" 285.437
"U 50 1933" (USC&GS) 290.357	Reference mark; 100 ft NW. of tablet; in NE. angle of
LINE 2.	crossroads; on concrete pipe culvert; chiseled square 288.02
FROM ELLERBE QUADRANGLE ALONG ROADS WEST TO POINT 10.5 MILES SOUTH OF MOUNT GILEAD (By W. S. Monk, 1954; Book AV 390 a)	FROM ELLERBE QUADRANGLE ALONG ROADS SOUTH TO POINT 7.2
"37 WSM 1954 268" (Described in line 1) 267.324	MILES SOUTH OF MOUNT GILEAD (By W. S. Monk, 1954; Book AV 390 a)
LINE 3.	"w 72 1934" (USC&GS) 477.542
FROM POINT 10.5 MILES SOUTH OF MOUNT GILEAD ALONG STATE HIGHWAY 109 NORTH INTO ELLERBE QUADRANGLE (By W. S. Monk, 1954; Book AV 390 a)	U.E., at Mount Gilead; 30 ft NW. of RR. crossing State Highway 109; on concrete base of warning signal; chiseled
"37 WSM 1954 268" (Described in line 1, also in line 2) 267.324	square 415.32
U.E., Mt. Gilead, 9.4 mi S. of; at steel girder bridge	Nt. Gilead; 850 ft W. of depot; 10 ft S. of, and 5 ft
crossing Pee Dee River; 15 ft E. of, and 5.0 ft lower	higher than S. rail; in concaete pier for overhead
than State Highway 109; 36 ft higher than river; on	bridge; standard tablet stamped "62 WSM 1954 419" 419.152
NE. concrete abutment; chiseled cross 215.27	

7 NORWOOD NORTH CAROLINA W. S. Monk	8 NORWOOD NORTH CAROLINA W. S. Monk Bk. AV 390 a 4/21/70 els
Bk. AV 390 a 4/21/70 els LINE 4 (Cont'd.)	LINE 4 (Cont.d.)
Reference mark; 25 ft S. of, and 20 ft higher than tablet;	U.E., Mt. Gilead, 3.2 mi S. of; at drain crossing; 20 ft
on SE. concrete abutment of overhead bridge; chiseled	E. of State Highway 109; on S. end of concrete headwall
cross 439.69	of culvert; chiseled cross 318.21
Mt. Gilead, 0.3 mi NW. of center of town; on property	Mt. Gilead, 3.8 mi S. of; 190 ft S. and 20 ft W. of, and
owned by United Mills; 194 ft W. of intersection of	3.0 ft lower than junction of State Highway 109 and
State Highways 73 and 109; 145 ft N. of NE. corner of	T-rd. W.; in center of concrete headwall of culvert;
United Mills building; 97 ft SW. of centerline of	standard tablet stamped "64 WSM 1954 325" 324.588
State Highway 73; 57 ft NE. of center of Mt. Gilead	Reference mark; 820 ft N. of tablet; 25 ft W. of center-
Municipal Water Tank; 52 ft SE. of center of entrance	line of hwy.; 100 ft N. of store; on N. end of concrete
drive; USC&GS standard triangulation disk stamped	headwall of culvert; chiseled cross 341.15
"MT GILEAD 1948" 433.278	U.E., Mt. Gilead, 5.1 mi S. of; 20 ft S. and 80 ft W. of,
Mt. Gilead, 0.3 mi NW. of center of town; on property	and 1.0 ft higher than junction of hwy, and rd. W.; in
owned by United Mills; 19 ft SE. of center of entrance	root on E. side of 40-in. oak tree; copper nail and
drive; 30 ft SW. of centerline of State Highway 73; in	washer 262.90
drill hole in NW. end of red brick retaining wall;	Mt. Gilead, 5.5 mi S. of; 60 ft S. and 30 ft W. of, and
USC&GS standard reference disk stamped	1.0 ft lower than junction of State Highway 109 and
"MT GILEAD NO 2 1948" 433.824	rd. SW.; 4.5 ft S. of telephone pole; in concrete post;
Mt. Gilead, 1.6 mi S. of; 25 ft E. of, and 4.0 ft lower	standard tablet stamped "65 WSM 1954 270" 269.644
than State Highway 109; 320 ft N. of, and level with	Reference mark; 500 ft N. of tablet; 20 ft E. of hwy.; on
junction of rd. W.; in center of concrete headwall of	concrete headwall of culvert; chiseled cross 266.93
culvert; standard tablet stamped "63 WSM 1954 402" 401.759	
Reference mark; 200 ft S. of tablet; 60 ft E. of center-	A A
line of hwy.; in face on SW. side of 10-in. oak tree;	
rail spike 408.88	

NORTH CAROLINA N. D. Leech LINE 5. LIN	NORWOOD	NORTH CAROLINA W. D. I.		10 NORWOOD NORTH CAROLINA W D Lee	
FROM POINT 0.3 MILE NORTHWEST OF MORNT GILEAD ALONG STATE 'GINAY 73 NORTHWEST THTO ALBEMARLE QUADRANGLE (By W. D. sch. 1955-56; Book AV 457 a) AT GILEAD 1948" (Described in line 4) This Elev. #33.347 Prev. Elev. #33.327 Glosure +.069 Reference mark No. 1; 85 ft E. of station; 29 ft SW. of centerline of State Highway 73; set flush in drill hole at SE. end of red brick retaining wall; USCMS standard reference disk stamped "MT GILEAD NO 1 1948" Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. #33.696 Glosure +.055 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. #33.696 Glosure +.055 Closure +.055 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. #33.697 Glosure +.055 Closure +.055 Cl		D. 20		Bk. AV 457 a 4/21/70 els	
Concrete pipe; chiseled square 318.144 AT GILEAD 1948" (Described in line 4) A33.347 AT GILEAD 1948" (Described in line 4) This Elev. 433.278 Closure +069 "MT GILEAD 2 1948" (Described in line 4) A33.893 Reference mark (200 ft NW. of tablet; 60 ft NE. of centerline of state Highway 73; set flush in drill hole at SE. end of red brick retaining wall; USCAOS (Described in line 4) Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 This Elev. 433.807 Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.807 This Elev. 435.807 This Elev. 435.8		LINE 5.	56	LINE 5 (Cont'd.)	5
concrete pipe; chiseled square 318.144 AT GILEAD 1948" (Described in line 4) A33.347 Prev. Elev. 433.276 Closure 433.893 Mt. Gilead, 2.0 mi NW. of; SW. of hwy.; on NW. end of wall of bridge over Clarks Creek; standard tablet stamped "1 MDL 1955 284" Reference mark; 210 ft NW. of tablet; 60 ft NE. of center- This Elev. 433.893 Prev. Elev. 433.893 Reference mark; 210 ft NW. of tablet; 60 ft NE. of center- line of hwy.; in root on E. side of 10-in. pine tree; copper nail and washer 276.486 U.E., at nail in bridge NE. of hwy. and rd. NE. to house, of centerline of State Highway 73; set flush in drill hole at SE. end of red brick retaining wall; USCMGS standard reference disk stamped "MT GILEAD NO 1 1948" Reference mark for "62 WSN 1954 419"; chiseled cross (Described in line 4) A39.746 Prev. Elev. 439.69 Closure A39.746 A39.	FROM POINT 0.3 MILE NORTHWE	ST OF MOUNT GILEAD ALONG STATE		U.E., at rd. fork NE.; N. of hwy.; on E. end of 18-in.	
This Elev. 433.347 Prev. Elev. 433.278 Closure +.069 "I WDL 1955 284" 284.115 "MT GILEAD NO 2 1948" (Described in line 4) 433.893 Reference mark; 210 ft NW. of tablet; 60 ft NE. of center- This Elev. 433.893 Prev. Elev. 433.893 Reference mark; 210 ft NW. of tablet; 60 ft NE. of center- This Elev. 433.894 Closure +.069 Reference mark No. 1; 85 ft E. of station; 29 ft SW. of centerline of State Highway 73; set flush in drill hole at SE. end of red brick retaining wall; USC&9S standard reference disk stamped "MT GILEAD No 1 1948" Reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 433.69 Closure +.055 U.E., NW. angle of rd. W. at Fairview Farms; on SW. corner of S. wall of L-shaped culvert; chiseled square 439.746 Prev. Elev. 433.69 Closure +.055 U.E., 190 ft NW. of junction of State Highway 27 and Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. corner of bottom brick step at entrance to house; chiseled square 403.860 do bridge over Clarks Creek; standard tablet stamped "1 WDL 1955 284" 284.115 284.115 284.115 284.115 A33.893 Reference mark; 210 ft NW. of tablet; 60 ft NE. of center- line of hwy.; in root on E. side of 10-in. pine tree; copper nail and washer U.E., at nail in bridge NE. of hwy. and rd. NE. to house, painted "344.1" Die., NW. angle of rd. W. at Fairview Farms; on SW. corner of S. wall of L-shaped culver; chiseled square 366.781 Albemarle, 12.6 mi SE. of; at junction of State Highways 439.746 Prev. Elev. 439.69 Closure 439.746 Prev. Elev. 439.69 Closure 46 ft W. of centerline of rd.; 43 ft E. of center- 1ine of Highway 73; 6 ft N. of white witness sign; in concrete post projecting 6-in.; USC&GS standard triangulation disk stamped "PEE DEE 1948" 440.202 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in	ech, 1955-56; Book AV 457	a)		concrete pipe; chiseled square	318.144
Prev. Elev. \$\frac{1}{3}3.278\$ Closure \$\frac{1}{1}0059\$ "I WDL 1955 284" **NT GILEAD NO 2 1948" (Described in line 4) **NT GILEAD NO 2 1948" (Described in line 4) **This Elev. \$\frac{1}{4}33.893\$ Prev. Elev. \$\frac{1}{4}33.893\$ Prev. Elev. \$\frac{1}{4}33.894\$ Prev. Elev. \$\frac{1}{4}33.894\$ Prev. Elev. \$\frac{1}{4}33.894\$ Closure \$\frac{1}{1}0059\$ **Reference mark No. 1; 85 ft E. of station; 29 ft SW. of centerline of State Highway 73; set flush in drill hole at SE. end of red brick retaining wall; USCAGS standard reference disk stamped "MT GILEAD NO 1 1948" Reference mark for "62 WSM 195k 419"; chiseled cross (Described in line 4) **This Elev. \$\frac{1}{4}39.746\$ Prev. Elev. \$\frac	AT GILEAD 1948" (Describe	d in line 4)	433.347	Mt. Gilead, 2.0 mi NW. of; SW. of hwy.; on NW. end of wall	
"I WDL 1955 284" "MT GILEAD NO 2 1948" (Described in line 4) "MT GILEAD NO 2 1948" (Described in line 4) This Elev. 433.893 Prev. Elev. 439.746 Prev. Elev. 439.746 Prev. Elev. 439.746 Prev. Elev. A39.746 Prev. Elev. 439.69 Closure +.056 U.E., at nail in bridge NE. of hwy. and rd. NE. to house, painted "344.1" Described in line 4) 432.552 Ju.E., NW. angle of rd. W. at Fairview Farms; on SW. corner Albemarle, 12.6 mi SE. of; at junction of State Highways Prev. Elev. 439.746 Prev. Elev. 439.69 Prev. Elev. A39.746 Prev. Elev. A39.69 Prev. Elev. A39				of bridge over Clarks Creek; standard tablet stamped	
This Elev. 433.893 Prev. Elev. 433.894 Closure 1.069 Reference mark No. 1; 85 ft E. of station; 29 ft SW. of centerline of State Highway 73; set flush in drill hole at SE. end of red brick retaining wall; USC&GS standard reference disk stamped "MT GILEAD No 1 1948" 432.552 (Described in line 4) This Elev. 439.746 Prev. Elev. 439.69 Closure 1.056 U.E., at nail in bridge NE. of hwy. and rd. NE. to house, painted "344.1" Jule., at nail in bridge NE. of hwy. and rd. NE. to house, painted "344.1" Jule., NW. angle of rd. W. at Fairview Farms; on SW. corner of S. wall of L-shaped culvert; chiseled square Albemarle, 12.6 mi SE. of; at junction of State Highways (Described in line 4) This Elev. 439.746 Prev. Elev. 439.69 Closure + 0.056 U.E., 190 ft NW. of junction of State Highway 27 and y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. corner of bottom brick step at entrance to house; chiseled square 403.860 Line of hwy.; in root on E. side of 10-in. pine tree; copper nail and washer U.E., at nail in bridge NE. of hwy. and rd. NE. to house, anall of hwy. and rd. NE. to house, anall of rd. W. at Fairview Farms; on SW. corner 344.085 U.E., NW. angle of rd. W. at Fairview Farms; on SW. corner 386.781 Albemarle, 12.6 mi SE. of; at junction of State Highways 439.746 27 and 73; in triangle formed by junction of two hwys. and paved cut-off rd. NESW. connecting them; 231 ft SE. of junction; 96 ft S. of centerline of Highway 27; 46 ft W. of centerline of cut-off rd.; 43 ft E. of center- 1 ine of Highway 73; 6 ft N. of white witness sign; in concrete post projecting 6-in.; USC&GS standard thiseled square 440.202 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in				"1 WDL 1955 284"	284.115
Closure Mark No. 1; 85 ft E. of station; 29 ft SW. of centerline of State Highway 73; set flush in drill hole at SE. end of red brick retaining wall; USC&GS standard reference mark for "62 WSN 195k 419"; chiseled cross (Described in line 4) This Elev. 439.746 Prev. Elev. 439.69 Closure +.056 U.E., at nail in bridge NE. of hwy. and rd. NE. to house, painted "344.1" U.E., NW. angle of rd. W. at Pairview Farms; on SW. corner of S. wall of L-shaped culvert; chiseled square Albemarle, 12.6 mi SE. of; at junction of State Highways 27 and 73; in triangle formed by junction of two hwys. and paved cut-off rd. NESW. connecting them; 231 ft SE. of junction; 96 ft S. of centerline of Highway 27; U.E., 190 ft NW. of junction of State Highway 27 and Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. corner of bottom brick step at entrance to house; chiseled square WO3.860 U.E., at nail in bridge NE. of hwy. and rd. NE. to house, painted "344.1" U.E., at nail in bridge NE. of hwy. and rd. NE. to house, painted "344.1" U.E., at nail in bridge NE. of hwy. and rd. NE. to house, and painted "344.1" U.E., at nail in bridge NE. of hwy. and rd. NE. to house, painted "344.1" U.E., at nail in bridge NE. of hwy. and rd. NE. to house, and painted "344.1" U.E., NW. angle of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. corner able of rd. W. at Pairview Farms; on SW. cor	"MT GILEAD NO 2 1948" (Des	cribed in line 4)	433.893	Reference mark; 210 ft NW. of tablet; 60 ft NE. of center-	
copper nail and washer copper				line of hwy.; in root on E. side of 10-in. pine tree;	
of centerline of State Highway 73; set flush in drill hole at SE. end of red brick retaining wall; USC&GS standard reference disk stamped "MT GILEAD NO 1 1948" Reference mark for "62 WSM 195½ 419"; chiseled cross (Described in line 4) This Elev. 439.746 Prev. Elev. 439.69 Closure +.0556 U.E., 190 ft NW. of junction of State Highway 27 and Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. U.E., at Y-rd. fork NW.; SW. of State Highway 27; in painted "344.1" Described "344.1" U.E., NW. angle of rd. W. at Fairview Farms; on SW. corner of S. wall of L-shaped culvert; chiseled square Albemarle, 12.6 mi SE. of; at junction of State Highways Albemarle, 12.6 mi SE. of; at junction of two hwys. 27 and 73; in triangle formed by junction of two hwys. SE. of junction; 96 ft S. of centerline of Highway 27; 46 ft W. of centerline of cut-off rd.; 43 ft E. of center- line of Highway 73; 6 ft N. of white witness sign; in concrete post projecting 6-in.; USC&GS standard chiseled square 403.860 U.E., NW. angle of rd. W. at Fairview Farms; on SW. Concrete post projecting formed by Junction of SW. and paved cut-off rd. NESW. connecting them; 231 ft SE. of junction; 96 ft S. of centerline of cut-off rd.; 43 ft E. of center- line of Highway 73; 6 ft N. of white witness sign; in concrete post projecting 6-in.; USC&GS standard triangulation disk stamped "PEE DEE 1948" 440.202				copper nail and washer	276.486
hole at SE. end of red brick retaining wall; USC&GS standard reference disk stamped "MT GILEAD NO 1 1948" Reference mark for "62 WSN 1954 419"; chiseled cross (Described in line 4) This Elev. 439.746 Prev. Elev. 439.69 Closure +056 U.E., NW. angle of rd. W. at Fairview Farms; on SW. corner and paved culvert; chiseled square 386.781 Albemarle, 12.6 mi SE. of; at junction of State Highways 439.746 27 and 73; in triangle formed by junction of two hwys. and paved cut-off rd. NESW. connecting them; 231 ft SE. of junction; 96 ft S. of centerline of Highway 27; U.E., 190 ft NW. of junction of State Highway 27 and 46 ft W. of centerline of cut-off rd.; 43 ft E. of center- Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. line of Highway 73; 6 ft N. of white witness sign; in concrete post projecting 6-in.; USC&GS standard chiseled square 403.860 U.E., NW. angle of rd. W. at Fairview Farms; on SW. corner 386.781 Albemarle, 12.6 mi SE. of; at junction of State Highways 439.746 27 and 73; in triangle formed by junction of two hwys. and paved cut-off rd. NESW. connecting them; 231 ft SE. of junction; 96 ft S. of centerline of cut-off rd.; 43 ft E. of center- Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. line of Highway 73; 6 ft N. of white witness sign; in concrete post projecting 6-in.; USC&GS standard triangulation disk stamped "PEE DEE 1948" 440.202	Reference mark No. 1; 85 ft	E. of station; 29 ft SW.		U.E., at nail in bridge NE. of hwy. and rd. NE. to house,	*
standard reference disk stamped "MT GILEAD NO 1 1948" Reference mark for "62 WSN 1954 #19"; chiseled cross (Described in line 4) This Elev. 439.746 Prev. 439.69 Closure +.056 U.E., 190 ft NW. of junction of State Highway 27 and Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. corner of bottom brick step at entrance to house; Chesc at Y-rd. fork NW.; SW. of State Highway 27; in Albemarle, 12.6 mi SE. of; at junction of State Highways Albemarle, 12.6 mi SE. of; at junction of State Highways Albemarle, 12.6 mi SE. of; at junction of State Highways Albemarle, 12.6 mi SE. of; at junction of two hwys. and paved cut-off rd. NESW. connecting them; 231 ft SE. of junction; 96 ft S. of centerline of Highway 27; He ft W. of centerline of cut-off rd.; 43 ft E. of centerline of Highway 73; 6 ft N. of white witness sign; in concrete post projecting 6-in.; USC&GS standard triangulation disk stamped "PEE DEE 1948" 440.202 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in	of centerline of State Hig	shway 73; set flush in drill	•	painted "344.1"	344.085
Reference mark for "62 WSM 1954 419"; chiseled cross (Described in line 4) 439.746 Prev. Elev. 439.69 Closure +.056 U.E., 190 ft NW. of junction of State Highway 27 and y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. corner of bottom brick step at entrance to house; chiseled square U.E., at Y-rd. fork NW.; SW. of State Highway 27; in	hole at SE. end of red br	ck retaining wall; USC&GS		U.E., NW. angle of rd. W. at Fairview Farms; on SW. corner	•
(Described in line 4) This Elev. #39.746 Prev. Elev. #39.69 Closure 439.69 Closure 439.69 Closure 46 ft W. of centerline of cut-off rd.; 43 ft E. of center- Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. corner of bottom brick step at entrance to house; chiseled square 439.746 Prev. Elev. #39.746 SE. of junction; 96 ft S. of centerline of Highway 27; Let W. of centerline of cut-off rd.; 43 ft E. of center- line of Highway 73; 6 ft N. of white witness sign; in concrete post projecting 6-in.; USC&GS standard chiseled square 403.860 403.860 403.860 403.860 403.860 403.860	standard reference disk st	amped "MT GILEAD NO 1 1948"	432.552	of S. wall of L-shaped culvert; chiseled square	386.781
This Elev. #39.746 Prev. Elev. 439.69 Closure +056 U.E., 190 ft NW. of junction of State Highway 27 and 46 ft W. of centerline of cut-off rd.; 43 ft E. of center- Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. line of Highway 73; 6 ft N. of white witness sign; in corner of bottom brick step at entrance to house; concrete post projecting 6-in.; USC&GS standard chiseled square 403.860 triangulation disk stamped "PEE DEE 1948" 440.202 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in	Reference mark for "62 WSM]	.954 419"; chiseled cross		Albemarle, 12.6 mi SE. of; at junction of State Highways	
Prev. Elev. 439.69 Closure +.056 SE. of junction; 96 ft S. of centerline of Highway 27; U.E., 190 ft NW. of junction of State Highway 27 and 46 ft W. of centerline of cut-off rd.; 43 ft E. of center- Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. line of Highway 73; 6 ft N. of white witness sign; in corner of bottom brick step at entrance to house; concrete post projecting 6-in.; USC&GS standard chiseled square 403.860 triangulation disk stamped "PEE DEE 1948" 440.202 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in	(Described in line 4)		439.746	27 and 73; in triangle formed by junction of two hwys.	
Closure +.056 SE. of junction; 96 ft S. of centerline of Highway 27; U.E., 190 ft NW. of junction of State Highway 27 and 46 ft W. of centerline of cut-off rd.; 43 ft E. of center- Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. line of Highway 73; 6 ft N. of white witness sign; in corner of bottom brick step at entrance to house; concrete post projecting 6-in.; USC&GS standard chiseled square 403.860 triangulation disk stamped "PEE DEE 1948" 440.202 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in				and paved cut-off rd. NESW. connecting them; 231 ft	
Y-rd. NW.; 50 ft NE. of centerline of rd.; on SW. corner of bottom brick step at entrance to house; chiseled square 403.860 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in				SE. of junction; 96 ft S. of centerline of Highway 27;	
corner of bottom brick step at entrance to house; concrete post projecting 6-in.; USC&GS standard chiseled square 403.860 triangulation disk stamped "PEE DEE 1948" 440.202 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in	U.E., 190 ft NW. of junction	of State Highway 27 and		46 ft W. of centerline of cut-off rd.; 43 ft E. of cente	r-
chiseled square 403.860 triangulation disk stamped "PEE DEE 1948" 440.202 U.E., at Y-rd. fork NW.; SW. of State Highway 27; in	Y-rd. NW.; 50 ft NE. of ce	nterline of rd.; on SW.		line of Highway 73; 6 ft N. of white witness sign; in	
U.E., at Y-rd. fork NW.; SW. of State Highway 27; in	corner of bottom brick ste	p at entrance to house;		concrete post projecting 6-in.; USC&GS standard	
	chiseled square		403.860	triangulation disk stamped "PEE DEE 1948"	440.202
root of 12-in. sycamore tree; copper nail and washer 296.535	U.E., at Y-rd. fork NW.; SW.	of State Highway 27; in		المر	7
	root of 12-in. sycamore tr	ee; copper nail and washer	296.535	TOP MOVE	Ex 21 "

II NORWOOD Bk. AV 457 b 4/21/70 els FROM POINT 1.0 MILE NORTHWN NORTHWEST THENCE SOUTHWEST (By W. D. Leech, 1955; Book	INTO STANFIELD QUADRANGLE	ech	12 NORWOOD NORTH CAROLINA W. D. Leed Bk. AV 457 b 4/21/70 els LINE 6 (Cont'd.) Aquadale, 2.0 mi N. of; 400 ft W. of crossroads; 50 ft W. of private rd. N.; 25 ft N. of centerline of rd.; in	
"K 50 1933" (USC&GS)	,	349.317	concrete post; standard tablet stamped "45 WDL 1955 515"	514.794
U.E., 0.2 mi S. of milepost	: 67; on SE. corner of W. copin		Reference mark; 320 ft W. of tablet; 30 ft S. of centerline	, , , ,
of culvert; chiseled squa	ire	398.856	of rd.; in root of 8-in. oak tree; copper nail and	
U.E., 50 ft N. and 20 ft E.	of rd. crossing; on NW. corne	•	washer (SE. angle of private rd. S.)	517.281
of concrete base of warni	ng signal; chiseled square	449.235	U.E., 30 ft NE. of junction of crossroad; in root of 12-in.	•
"J 50 1933" (USC&GS) (Rep	orted disturbed, 1957)	448.143	oak tree; copper nail and washer	522.249
This Elev. 448.143 USC&GS Elev. 448.159			Elev. of Road N. = 495 ft	
Closure016			Aquadale, 1.5 mi NW. of; 180 ft W. of crossroads; 25 ft	
U.E., 30 ft W. and 25 ft S.	of RR. crossing; on concrete		S. of centerline of rd.; in concrete post; standard	
pipe		459.987	tablet stamped "46 WDL 1955 488"	487.983
Aquadale, 2.0 mi N. of, the	nce 2.0 mi E.; 100 ft W. of		Reference mark; 90 ft W. of tablet; in root of double pine	
crossroads; 25 ft N. of r	d.; in concrete post; standard		tree; copper nail and washer	488.814
tablet stamped "44 WDL 19	55 479"	479.277	U.E., 30 ft E. and 25 ft N. of junction of private rd. E.;	
Reference mark; 80 ft E. of	tablet; 30 ft S. of centerline	•	in root of oak tree; copper nail and washer	470.847
of rd.; in root of 10-in.	maple tree; copper nail and		U.E., in center of W. side of wooden bridge over RR.; copp	er
washer		474.936	nail and washer	461.949
Elev.	of crossroads = 540 ft	-	Oakboro, 4.9 mi E. of; 300 ft NE. of bridge over Long Creek	: ;
U.E., 30 ft N. of centerlin	e of rd.; 20 ft E. of woods rd.		60 ft N. and 40 ft E. of centerline of T-rd. N.; in	
S.; in root of 10-in. pin	e tree; copper nail and washer	570.864	concrete post; standard tablet stamped "47 WDL 1955 297"	296.931
			Reference mark; 410 ft SW. of tablet; 25 ft E. of W. end of	
			bridge; on N. side; on concrete pier; chiseled square	292.302

13 NORW Bk. AV 1557	c,d 4/22/70 els	Zohn, Jr.			WOOD NORTH CAROLINA 7 c,d 4/22/70 els	H. L. Zohn,	Jr.
	LINE 7.	1969	LIN	7 (Co	nt'd.)	1969	
FROM PAGELA	ND QUADRANGLE ALONG ROADS NORTH TO BURNSVILLE HEAST ABOUT 2.2 MILES THENCE SOUTHEAST TO	3	3 5	6 4.2	B Peachland, 0.6 mi N. of post off	ice, along	
ANSONVILLE	(By H. L. Zohn, Jr., 1969; Books AV 1557 c,d)				County Road 1240, thence 0.2 mi	W. along	
3 50 0.00	"F 51 1933" (USCAGS)	446.022			County Road 1404, thence 3.4 mi	N. along	
·	This Elev. 446.022 USC&GS Elev. 446.023	e in gra			County Road 1411; at C. Jackson'	s store;	
24.1	Closure001	44,			in concrete base for Gulf sign;	standard	N -
3 50 0.56	U.E., in junction of County Roads 1404 and	erger og jord			tablet stamped "244 HLZ 1969", p	ainted "BM"	503.394
	1240; copper nail and washer, painted "CL"	388.350	3 5	7 4.7	7 U.E., in junction of County Road	s 1443 and	دئى توجم
3 52 1.58	Peachland, 0.6 mi N. of post office, along				1446; copper nail and washer, pa	inted "CL"	497.973
	County Road 1240, thence 0.2 mi W. along		3 5	8 5.3	7 Peachland, 0.6 mi N. of post off	ice, along	
	County Road 1404, thence 0.8 mi N. along	er engage			County Road 1240, thence 0.2 mi	W. along	1.4
	County Road 1411; 60 ft NNW. of, and about	N			County Road 1404, thence 3.4 mi	f. along	e 15
." [49.4	2.0 ft lower than junction of County Roads				County Road 1411, thence 1.1 mi	NE. along	* 1
	1411 and 1406; 0.5 ft S. of witness sign;				County Road 1443; 1.0 ft SE. of	telephone	
	in concrete post projecting 2-in.; standard			jira nga	pole; 40 ft NW. of, and about 1.	oft lower	
	tablet stamped "242 HLZ 1969", painted "BM"	433.002			than junction of County Roads 14	43 and 1445	
53 2.20	U.E., in junction of County Roads 1411 and	eng of the second			N.; in concrete post projecting	3-in.; standard	1
	1407; copper nail and washer, painted "CL"	432.351			tablet stamped "245 HLZ 1969", p	ainted "BM"	467.628
54 2.70	Peachland, 0.6 mi N. of post office, along		3 5	9 6.1	5 U.E., in junction of County Road	s 1002 and	
	County Road 1240, thence 0.2 mi W. along				1443; copper nail and washer, pa	inted "CL"	490.464
. e	County Road 1404, thence 1.8 mi N. along		3 6	6.7	U.E., in junction of County Road	s 1444 and	
	County Road 1411; at Austin's store; in				1450; copper nail and washer, pa	inted "CL"	448.416
	center of Gulf gas pump base; standard table	et			3 V 100 0 2 3 P 1 5 5 0 0 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	atas melakan	
	stamped "243 HLZ 1969", painted "RM"	461.736					

Elevations

WL = 259 ft

15 NORWOOD NORTH CAROLINA H. L. Zohn Bk. AV 1557 c,d 4/22/70 els LINE 7 (Cont'd.) 1969	, Jr.	16 NORW Bk. AV 1557 LINE 7 (Con	c,d 4/22/70 els	
3 61 7.10 Burnsville, 0.9 mi SE. of junction of State Highway 742 and County Road 1456, along Highway 742, thence 1.4 mi SW. along County	State of the State	3 66 9.44	Burnsville; at Thomas's store; in W. end of concrete base for Atlantic gas pumps; standar tablet stamped "248 HLZ 1969", painted "BM"	
Road 1444; at 30-ft bridge over Cribs Creek; in NE. wingwall; standard tablet stamped "246 HLZ 1969", painted "BM"	401.301	3 67 10.23	U.E., in junction of County Road 1610 and dirt field rd. N.; copper nail and washer,	497.022
WL = 391 ft 3 62 7.33 U.E., in junction of County Roads 1444 and	**************************************	3 68 10.83	Highway 742 and County Road 1610, along	488.403
1451; copper nail and washer, painted "CL" 3 63 8.03 U.E., in centerline of 18-ft wooden bridge over small stream; copper nail and washer,	472.959		County Road 1610; 80 ft S. of, and about 1.5 ft higher than junction of County Roads 1610 and 1611; 1.0 ft N. of witness sign;	
painted "CL" WL = 395 ft 3 64 8.53 Brunsville, 0.9 mi SE. of junction of State	401.217	2 60 11 62	in concrete post projecting 3-in.; standard tablet stamped "249 HLZ 1969", painted "BM"	394.080
Highway 742 and County Road 1456, along Highway 742; 2.0 ft S. of power pole; 98			U.E., in junction of County Roads 1610 and 1600; 6-in. steel rod, painted "CL" U.E., in junction of County Roads 1600 and	383.796
ft S. of, and about level with junction of Highway 742 and County Road 1444; in concrete post projecting 5-in.; standard tablet stamped "247 HLZ 1969", painted "BM"	446.775	3 71 12.62	1612; copper nail and washer, painted "CL" Burnsville, 2.2 mi NE. of junction of State Highway 742 and County Road 1610, along	333.471
3 65 8.98 U.E., in junction of State Highway 742 and County Road 1452 W.; copper nail and washer, painted "CL"	474.834		Road 1610, thence 0.5 mi SE. along County Road 1600, thence 0.5 mi E. along County Road 1612; at 40-ft bridge over Cribs Creek; in SE. end of NE. backwall; standard tablet stamped "250 HLZ 1969", painted "BM"	268.899

	17 AV	WORWOOD	,d 4/22/70 els	Jr.	В	l Sk.	NORWO	OOD NORTH CAROLINA E. L. Zohn,	Jr.
LIN	E 7	(Cont'	<u>d.)</u>		Ī	INE	7 (Cont	1969	
	7 2	13.03	U.E., in junction of County Roads 1610		3	7	7 16.62	Ansonville, 2.0 mi W. of United Methodist	
			and 1612; copper nail and washer, painted					Church, along County Road 1418, thence 0.3	
			"CL"	365.547				mi N. along County Road 1618; at lookout	
3 '	7 3	13.51	Burnsville, 2.2 mi NE. of junction of State					tower; in concrete base for steps leading	
			Highway 742 and County Road 1610, along					up tower; standard tablet stamped	
			Road 1610, thence 0.5 mi SE. along County					"253 HLZ 1969", painted "BM"	430.059
			Road 1600, thence 1.5 mi E. along County		3	78	16.90	U.E., in junction of County Roads 1418	
			Road 1612; at 200-ft bridge over Lanes					and 1618; copper nail and washer, painted	
			Creek; in NE. end of NW. backwall; standard					"CL"	388.185
			tablet stamped "251 HLZ 1969", painted "BM"	254.028	4	5	17.69	Ansonville, 1.2 mi W. of United Methodist	
			WL = 230 ft					Church, along County Road 1418; at Pleasant	
3 7	74	14.27	U.E., in junction of County Roads 1612 and					Hill Church; 15 ft W. of SW. corner of	
			1613; copper nail and washer, painted "CL"	355.455				church; in SE. corner of concrete basefor	
3 7	75	14.99	Ansonville, 2.0 mi W. of United Methodist					bell; standard tablet stamped "254 HLZ 1969"	
			Church, along County Road 1418, thence 1.1					painted "BM"	331.536
			mi NNW. along County Road 1618, thence 1.0		4	6	18.30	U.E., in junction of County Roads 1418 and	
			mi MNW. along County Road 1619; at Gulf					1620; copper nail and washer, painted "CL"	293.190
			Service Station; in W. end of concrete base		4	7	18.70	"S 50 1933" (USC&GS)	306.423
			for gas pumps; standard tablet stamped					This Elev. 306.423	
			"252 HLZ 1969", painted "BM"	404.181				USC&GS Elev. 306.184 Closure +.239	
3 7	6	15.85	U.E., in junction of County Roads 1619 and		4	8	19.31	"R 50 1933" (USC&GS)	324.792
			1618; copper nail and washer, painted "CL"	419.937				This Elev. 324.792 USCAGS Elev. 324.586 Closure +.206 NGVD 29	

Elevations

19 NORWOOD NORTH CAR Bk. AV 1557 d 4/22/70 els LINE 8.	DLINA H. L. Zohn, Jr. 1969	Bk. AV	NORWO	d 4/22/70 els	L. Zohn, Jr. 1969
FROM STANFIELD QUADRANGLE ALONG ROADS (By H. L. Zohn, Jr., 1969; Book AV 155	EAST TO BURNSVILLE			Burnsville, 2.2 mi NE. of junction of St	tate
4 30 7.65 U.E., in centerline of 18	<u> </u>			Highway 742 and County Road 1610, along Road 1610, thence 1.05 mi NNW. along Cou	intv
over Pine Creek; copper r	•	9.883		Road 1600; 37 ft NE. of, and about 2.0 f	ft
WL = 383 f	't			lower than junction of County Roads 1600 1607; 0.5 ft W. of witness sign; in cond	
4 31 8.43 U.E., in junction of Coun 1445; copper nail and was 4 32 8.83 "248 HLZ 1969" (Describe	her, painted "CL" 515.	5.229 7.088 4 43	1 70	post projecting 4-in.; standard tablet stamped "261 HLZ 1969", painted "BM"	342.699
This Elev. 497.088 Prev. Elev. 497.022 Closure +.066 LINE 9.		4 43	1.70	dirt rd. SW.; copper nail and washer, painted "CL"	267.267
FROM POINT 2.2 MILES NORTHEAST OF BURN ROADS NORTHWEST INTO STANFIELD QUADRAN Jr., 1969; Book AV 1557 d)	GLE (By H. L. Zohn,	1 44	1.95	Burnsville, 2.2 mi NE. of junction of St Highway 742 and County Road 1610, along Road 1610, thence 2.0 mi NW. along County	
4 40 0.00 U.E., at rd. junction; 6- (Described in line 7) 4 40 0.38 U.E., in junction of Coun	383.	.796		Road 1600; at 180-ft bridge over Richard Creek; in NE. end of NW. backwall; stand	ison lard
1608; copper nail and was			0.06	tablet stamped "262 HLZ 1969", painted ' WL = 235 ft U.S. 45 investor of County Read 1600 as	
over small stream; copper painted "CL"	301.9		2.96	U.E., in junction of County Road 1600 and drive NE. to residence of D. Turner; connail and washer, painted "CL"	

WL = 294 ft

LINE 9 (Cont'd.)

Highway 742 and County Road 1610, along
Road 1610, thence 3.4 mi NW. along County
Road 1600; 105 ft S. of, and about 0.3 ft
lower than junction of County Roads 1600
and 1606; 0.5 ft NW. of witness sign; in
concrete post projecting 4-in.; standard
tablet stamped "263 HLZ 1969", painted "EM"

427.809

4 48 3.75 U.E., in junction of County Roads 1600 and 1603; copper nail and washer, painted "CL"

435.909

4 50 4.50 U.E., in junction of County Roads 1600 and

1601; copper nail and washer, painted "CL"

404.700